

Specifications

Tight Rope

466760

Application

Seating

Characteristics

Content: 100% Polyurethane

Finish: None

Backing: Polyester

Width: 54" (137cm)

Repeat: 6 3/4" V, 6 3/4" H
(17cm V, 17cm H)

Bolt Size: 30 yards (27 m)

Weight: 18 oz/ly (600 gr/lm)

Country of Origin: Taiwan

Price

Contact your sales representative for pricing.

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Testing

Abrasion: ASTM D4157, 100,000 double rubs Wyzenbeek

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Multiple factors affect fabric durability and appearance retention.

Flammability: CAL 117-2013

NFPA 260

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Tight Rope

466760

Environmental


- Greenguard Gold Certified
- LBC Red List Free
- FR Free
- Free of Intentionally Added PFAS

Warranty


5 years.

© 2014 Knoll, Inc.


Complete product information at knolltextiles.com
800.645.3943




001 Pathway




002 Sparrow




003 Harvest




004 Spearmint



005 Horizon



008 Nickel



009 Artifact