

Specifications

Viewpoint

300166

Application

Upholstered Walls, Walls

Characteristics

Content: 51% Post-Consumer Recycled Polyester, 28% Polyester, 21% Polyolefin

Finish: Stain Repellent

Backing: Acrylic

Width: 56" (142cm)

Bolt Size: 60 yards (55 m)

Weight: 12.8 oz/ly (400 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

Testing

Acoustics: ASTM C423, 0.85 NRC

Flammability: ASTM E84 Adhered

ASTM E84 Unadhered

CAN ULC S102 Adhered

EN 13501 Unadhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Viewpoint
300166


Knoll Textiles

Environmental
Greenguard Gold Certified
GRS Certified Content
Contains Recycled Content
FR Free

Warranty
10 years.

© 2022 Knoll, Inc.


Complete product information at knolltextiles.com
800.645.3943




001 Daisy



002 Cloudscape




003 Volcano



004 Caterpillar



005 Bluebonnet



006 Wicker



007 Lunar