



Product Specifications

|                     |                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------|
| Construction        | Textured Loop                                                                                        |
| Backing             | PremierBac® Plus                                                                                     |
| Dye Method          | Solution Dyed                                                                                        |
| Fiber Type          | TeraPlex® SD PET with Encore® SD Nylon                                                               |
| Face Weight         | 22 oz./sy (746 grams/m2)                                                                             |
| Pile Density        | 8250 oz./y3 (305.92 kg/m3)                                                                           |
| Pattern Repeat      | N/A                                                                                                  |
| Gauge               | 1/8 (3.15 rows/cm)                                                                                   |
| Stitches Per Inch   | 7.33 stitches/in (2.89 stitches/cm)                                                                  |
| Standard Width      | 12 ft 3.66 m                                                                                         |
| Standard Adhesive   | Commercialon Premium Carpet Adhesive                                                                 |
| Standard Warranties | Commercialon Premium Broadloom Adhesive<br>PremierBac Plus<br>TeraPlex® SD PET with Encore® SD Nylon |

Special Technologies

|                        |          |
|------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release   | Standard |
| Sentir® Odor-Blocker   | Optional |

Environmental Specifications & Tests

|                        |                                    |
|------------------------|------------------------------------|
| NSF 140:               | Gold Certified                     |
| Total Recycled Content | 42%                                |
| Radiant Panel          | Class 1                            |
| Smoke Density          | Less then 450 flaming (ASTM E 662) |
| Static Test            | Less then 3 kv (AATCC-134)         |
| ADA Compliance         | Compliant For Accessible Routes    |
| Pill Test              | Yes                                |
| Lightfastness          | Yes                                |

Colorways



RMX15 Pebble



RMX47 Aniline




RMX54 Silver Grey



RMX55 Cinder



RMX56 Dusk



RMX58 Charcoal



RMX76 Coffee