J+J FLOORING

Serene | 6592

Product Specifications

Construction	Tip Sheared Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	7650 oz./y3 (283.67 kg/m3)
Pattern Repeat	72.00" (w) x 55.00" (l) approx. (182.88cm x 139.70cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	10.33 stitches/in (4.07 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	**PremierBac Plus** **Commercialon Premium Broadloom Adhesive** **Encore® SD Ultima Fiber**
Optional Warranties	**Endure Plus** **TitanBac Plus** **Encore® 100 Fiber**

Special Technologies

ProSept® Antimicrobial	Standard
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	33.4%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

3228 Sky


3229 Soft Grey

3230 Pine

3231 Teal

3232 Coffee

3233 Terra

3234 Sailor

3235 Meadowla...

3236 Sandstone

3237 Smoke