



#### Product Specifications

|                            |                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>        | Textured Loop                                                                                                        |
| <b>Backing</b>             | PremierBac® Plus                                                                                                     |
| <b>Dye Method</b>          | Solution Dyed                                                                                                        |
| <b>Fiber Type</b>          | Encore® SD Ultima® (with recycled content)                                                                           |
| <b>Face Weight</b>         | 20 oz./sy (678 grams/m2)                                                                                             |
| <b>Pile Density</b>        | 5441 oz./y3 (201.76 kg/m3)                                                                                           |
| <b>Pattern Repeat</b>      | .25" (w) x .25" (l) approx. (.64cm x .64cm)                                                                          |
| <b>Gauge</b>               | 1/10 (3.94 rows/cm)                                                                                                  |
| <b>Stitches Per Inch</b>   | 8 stitches/in (3.15 stitches/cm)                                                                                     |
| <b>Standard Width</b>      | 12 ft 3.66 m                                                                                                         |
| <b>Standard Adhesive</b>   | Commercialon Premium Carpet Adhesive                                                                                 |
| <b>Standard Warranties</b> | <b>PremierBac Plus</b><br><b>Commercialon Premium Broadloom</b><br><b>Adhesive</b><br><b>Encore® SD Ultima Fiber</b> |
| <b>Optional Warranties</b> | <b>Endure Plus</b><br><b>TitanBac Plus</b><br><b>Encore® 100 Fiber</b>                                               |

#### Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>ProTex® Soil Release</b>   | Standard |
| <b>Sentir® Odor-Blocker</b>   | Optional |


#### Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Total Recycled Content</b> | 34.21%                             |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |


#### Colorways



1800 Camber




1801 Pilaster



1802 Gambrel




1804 Truss



1805 Joist




1806 Spandrel



3397 Bracket



3398 Portico



3399 Transom