



Product Specifications

Construction	Bio-Based Commercial Rated Heterogeneous Urethane
Backing	Bio-Based Resilient
Thickness	2.2mm
Pattern	10 Tiles
Dimensions:	20cm x 120cm approx. (7.87402" x 47.2441")
Standard Adhesive	Purfix UltraTech Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	Bio-Based Resilient PurFix UltraTech Adhesive

Packaging

Sq.ft. per piece / carton	2.58 / 59.38
Weight per piece / carton	1.56 (lbs) / 35.86 (lbs)
Pieces per box	23
Boxes per pallet	60

Special Technologies


Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class	Class ASTM F3404
Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes
ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
ASTM F1914 (Residual Indentation)	Passes
ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes

Colorways




1160 Recycle




1161 Convert



1162 Salvage




1163 Beneficial




1164 Reuse



1165 Take Back



1166 Modify



1167 Alter