



Product Specifications

|                     |                               |
|---------------------|-------------------------------|
| Construction        | Textile Composite             |
| Backing             | Polyester Felt Cushion        |
| Dye Method          | Solution Dyed                 |
| Wear Layer          | Polyester - Applied Pattern   |
| Pattern Repeat      | N/A                           |
| Total Weight        | 4.5 oz - 5.2 oz/ square foot  |
| Total Thickness     | .205 inches                   |
| Dimensions:         | 18" x 36" modules             |
| Standard Adhesive   | Kinetex Adhesive              |
| Packaging           | 16 modules per box (72 sq.ft) |
| Standard Warranties | Kinetex Adhesive<br>Kinetex   |

Special Technologies


|                 |          |
|-----------------|----------|
| Kinetex ProTex® | Standard |
|-----------------|----------|

Environmental Specifications & Tests

|                         |                                    |
|-------------------------|------------------------------------|
| Carbon Footprint:       | Carbon Neutral                     |
| Recyclability:          | 100% Closed-loop Recyclable        |
| NSF 140:                | Platinum Certified                 |
| Indoor Air Quality      | GLP2690                            |
| Total Recycled Content: | 45%                                |
| Radiant Panel           | Class 1                            |
| Smoke Density           | Less then 450 flaming (ASTM E 662) |
| Static Test             | Less then 3 kv (AATCC-134)         |
| ADA Compliance          | Compliant For Accessible Routes    |
| Pill Test               | Yes                                |
| Lightfastness           | Yes                                |

**Installation Methods:** Parquet, Herringbone, Basketweave, Brick, Ashlar


Colorways




3400 Confident



3401 Poised



3402 Smooth



3403 Composed



3405 Urbane