


Installation Method



Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product	B601	Color	Black Sea	Collection	Net Effect Collection	Backing	GlasBac™
Product Specifications							
Product Number	1266502500						
Product Construction	Engaged Tufted Pattern Loop						
Yarn System	100% Recycled Content Nylon						
Yarn Manufacturer	Aquafil						
Dye Method	100% Solution Dyed						
Soil/Stain Protection	Protek2®						
Preservative Protection	Intersept®						
More Product Specifications							
		Imperial		Metric			
Tufted Yarn Weight	30 oz/yd ²			1,017 g/m ²			
Machine Gauge	1/10 in			39.4 ends/10cm			
Pile Height	0.29 in			7.40 mm			
Pile Thickness	0.23 in			5.00 mm			
Stitches	7.00 /in			27.55 ends/10cm			
Pile Density	4,737 oz/yd ³			175,647 g/m ³			
Size	19.69 in x 19.69 in			50cm x 50cm			
Performance Specifications							
Flooring Radiant Panel	(ASTM E-648) Passes						
Smoke Density	(ASTM E-662) ≤ 450						
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)						
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's						
Static	(AATCC - 134) < 3.0 KV						
Dimensional Stability	AACHEN Din 54318 < 0.10%						
Traffic Classification	Moderate						
Fiber Modification Ratio	1.9 to 2.2						
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition						
Health + Environmental Specifications							
Embodied Carbon (Cradle to Gate)	5.56 Kg CO ₂ /M ²						
Total Recycled Content	71.37 %						
Recycled Content (Pre Consumer)	57.29 %						
Recycled Content (Post Consumer)	14.08 %						
Indoor Air Quality	Green Label Plus #GLP0820						
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.						
Disclosure of Environmental Impacts	Environmental Product Declaration						
Disclosure of Product Ingredients	Health Product Declaration						
Environmental Certifications	NSF/ANSI 140 Gold						
LEED v4	Contributes to multiple IEQ and MR credits						
End of Life	Carpet to Carpet Recycling through ReEntry®						
Technical Information							
Installation	Interface Installation Guidelines						
Maintenance	Recommended Interface Maintenance Guidelines						
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)						
Warranty	15 Year Standard Carpet Warranty						
Installation Method	Non Directional						
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States						