




#### Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Third Space 302 **Color** Charcoal **Collection** Third Space Collection **Backing** GlasBac™

#### Product Specifications

Product Number	1680602500
Product Construction	Engaged Tufted Pattern Loop
Yarn System	100% Recycled Content Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt <sup>2</sup> ®
Preservative Protection	Intersept®

#### More Product Specifications

	Imperial	Metric
Tufted Yarn Weight	23 oz/yd <sup>2</sup>	780 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.16 in	4.10 mm
Pile Thickness	0.10 in	2.70 mm
Stitches	8.00 /in	31.49 ends/10cm
Pile Density	7,886 oz/yd <sup>3</sup>	292,411 g/m <sup>3</sup>
Size	19.69 in x 19.69 in	50cm x 50cm

#### Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.9 to 2.2
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

#### Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	5.01 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	69.56 %
Recycled Content (Pre Consumer)	57.97 %
Recycled Content (Post Consumer)	11.58 %
Indoor Air Quality	Green Label Plus #GLP0820
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	<a href="#">NSF/ANSI 140 Gold</a>
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Carpet to Carpet Recycling through ReEntry®

#### Technical Information

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	View recommended Interface Maintenance guidelines online
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Installation Method	Monolithic
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>