



Installation Method



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Tokyo Texture **Color** Ash **Collection** Embodied Beauty Collection **Backing** CQuest™BioX

Product Specifications

Product Number	137460AK0Q
Product Construction	Tufted Textured Loop
Yarn System	Post-Consumer Content Nylon
Yarn Manufacturer	Universal
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt ² ®
Preservative Protection	No Added Preservatives

More Product Specifications

	Imperial	Metric
Tufted Yarn Weight	12 oz/yd ²	407 g/m ²
Machine Gauge	1/12 in	47.2 ends/10cm
Pile Height	0.13 in	3.30 mm
Pile Thickness	0.05 in	1.20 mm
Stitches	14.70 /in	57.87 ends/10cm
Pile Density	9,000 oz/yd ³	333,718 g/m ³
Size	9.845 in x 39.38 in	25cm x 1m

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Severe
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	K2

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	-0.37 Kg CO ₂ /M ²
Biobased Content	Interface Modular Carpet on CQuestBioX contains 74% USDA certified biobased content
Total Recycled Content	27.65 %
Recycled Content (Pre Consumer)	26.94 %
Recycled Content (Post Consumer)	0.71 %
Indoor Air Quality	Green Label Plus #100244
Material Composition	PVC-free and also free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	Cradle to Cradle Certified® v3.1 Silver
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Reclaimed through ReEntry®

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Reclaim through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty
Installation Method	Herringbone
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States