


**Installation Method**

Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Vintage Kimono **Color** Coal **Collection** Embodied Beauty Collection **Backing** GlasBac™

Product Specifications

Product Number	141780AK00
Product Construction	Engaged Tufted Sheared
Yarn System	Post-Consumer Content Nylon
Yarn Manufacturer	Universal
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protek2®
Preservative Protection	Intersept®

More Product Specifications

	Imperial	Metric
Tufted Yarn Weight	26 oz/yd ²	882 g/m ²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.16 in	4.10 mm
Pile Thickness	0.10 in	2.50 mm
Stitches	8.70 /in	34.25 ends/10cm
Pile Density	9,551 oz/yd ³	354,149 g/m ³
Size	9.845 in x 39.38 in	25cm x 1m

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	5.25 Kg CO ₂ /M ²
Total Recycled Content	64.81 %
Recycled Content (Pre Consumer)	63.49 %
Recycled Content (Post Consumer)	1.32 %

Indoor Air Quality [Green Label Plus #GLP0820](#)

Material Composition Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.

Disclosure of Environmental Impacts [Environmental Product Declaration](#)

Disclosure of Product Ingredients [Health Product Declaration](#)

Environmental Certifications [NSF/ANSI 140 Gold](#)

LEED v4 Contributes to multiple IEQ and MR credits

End of Life Carpet to Carpet Recycling through ReEntry®

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty
Installation Method	Ashlar Herringbone
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States