


**Installation Method**

Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Steady Stride Woodgrains 3.0 mm **Color** Biscuit

**Product Specifications**

Product Number	B001
Product Construction	High Performance Luxury Vinyl Tile
Class / ASTM F1700	Class III Printed Vinyl Tile
Wear Layer Thickness	20 MIL
Total Thickness	3.0 mm
Backing Class	Commercial Grade
Finish	Ceramor™
Nominal Dimensions	12.5 cm x 1 m (4.923 in x 39.38 in)

**Performance Specifications**

IIC Sound Rating	(ASTM E492-09) 56 IIC
Slip Resistance	(ASTM D2047) >0.55 wet/dry, ADA Compliant
Static Load Limit	(ASTM F970) 1000 psi
Flexibility	(ASTMF137) Passes
Resistance to Heat	(ASTM F1514) Passes
Resistance to Light	(ASTM F1515) Passes
Radiant Flux	(ASTM E648) Class I
Smoke Density	(ASTM E-662) ≤ 450
Size & Squareness	(ASTM F2055) Passes, +/- 0.016 in. per linear foot
Thickness	(ASTM F386) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes

**Health + Environmental Specifications**

Embodied Carbon (Cradle to Gate)	7.27 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content (Pre Consumer)	39%
Indoor Air Quality	GREENGUARD Gold FloorScore® SCS-FS-04366 CDPH 01350 compliant
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	NSF/ANSI 332
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR

**Packaging**

Quantity per Carton	37.67 ft <sup>2</sup> (3.5 m <sup>2</sup> )
Pieces per Carton	28
Weight Per Carton	42 lb (19 kg )
Cartons per Pallet	44
Pallets per Truckload	20

**Technical Information**

Installation	<a href="#">Interface LVT Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface LVT Maintenance Guidelines</a>
Warranty	<a href="#">15 Year Standard LVT Warranty</a>
Installation Method	Ashlar Herringbone