



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product norament 992 grano **Color** Black Pepper **Collection** nora Rubber **Format** Tile **Surface** Hammered **Product Options** Standard **Thickness** 9.0mm

Product Specifications	
Article Number	1955
Surface	Hammered
Total Thickness	9 mm
Format	Tile
Size	39.45 in x 39.45 in
Performance Specifications	
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level
Radiant Flux (ASTM E648)	Class 1
Resistance to Oil & Grease (ISO 26987)	Passes
Packaging	
Quantity per Piece	10.7639 ft ² (1.0 m ²)
Weight per Piece	27.6 lbs
Technical Information	
Wheel Types	No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A ≤90
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.
Manufacturing Location	ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany