



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product norament arago **Color** Fortitude **Collection** norament **Format** Tile **Surface**
 Relief Structure **Product Options** Standard **Thickness** 3.5mm

Product Specifications	
Article Number	3118
Construction	Homogeneous Rubber Compound
Class	ASTM F1344 Standard Specification for Rubber Floor Tile
Surface	Relief Structure
Total Thickness	3.5 mm
Format	Tile
Size	39.53 in x 19.76 in
Performance Specifications	
ΔIIC Sound Rating (ASTM E2179)	ΔIIC 18
ΔLw Sound Rating (ISO 10140-3)	ΔLw 10 dB
Slip Resistance (ASTM D2047)	>0.5 dry/wet required, ADA Compliant
Bacteria Resistance (ASTM 2180/ASTM G21)	Resistant to bacteria, fungi and micro-organism activity
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level
Hardness (ASTM 2240)	Shore type A
Static Load Limit (ASTM F970)	≤ 0.005 in with 250 lbs required, Passes @ 800 psi
Rolling Load Limit (ASTM F2753)	≤ 850 lbs/sq in; for forklift traffic nora polyurethane adhesive is required
Abrasion Resistance (ASTM D3389)	≤ 0.035 oz (1.0 g) required, Passes
Resistance to Heat (ASTM F1514)	Passes
Radiant Flux (ASTM E648)	Class 1
Smoke Density (ASTM E662)	< 450
Size & Squareness (ASTM F2055)	Passes
Thickness (ASTM F386)	Passes
Dimensional Stability (ASTM F2199)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Resistance to Oil & Grease (ISO 26987)	Passes
Static Generation (AATCC 134)	< 1000 Volts at 20% RH
Thermal Transmission (ASTM C518)	R-value of -0.90
Health + Environmental Specifications	
Embodied Carbon (Cradle to Gate)	14.1 kg CO ₂ /M ²
Indoor Air Quality	Greenguard Gold
Material Composition	PVC-free and also free of added Formaldehyde, Heavy Metal Stabilizers and Ortho Phthalates and Halogenated Flame Retardants
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	Cradle to Cradle v3.1 Silver Greenhealth Approved PEFC Certified
LEED	Contributes to multiple IEQ and MR Credits
Packaging	
Quantity per Piece	10.7639 ft ² (1.0 m ²)
Weight per Piece	5.8 lbs
Technical Information	
Installation	nora Installation Guidelines
Maintenance	Recommended nora Maintenance Guidelines
Warranty	15 Year Standard Warranty

Installation Method	Directional
Wheel Types	No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A ≤ 90
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.
Manufacturing Location	ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany

Downloads

nora Guide Spec	Download Guide Spec
nora Flyer	Download Flyer
nora Viewbook	Download Viewbook