



www.interface.com/disclaimer.

Product	nomarment pado	Color	Coronet	Collection	nomarment	Format	Tile	Surface
Two-Tone	Product Options	Standard	Thickness	3.5mm				
Product Specifications								
Article Number	3167							
Construction	Homogeneous Rubber Compound							
Class	ASTM F1344 Standard Specification for Rubber Floor Tile							
Surface	Two-Tone							
Total Thickness	3.5 mm							
Format	Tile							
Size	39.53 in x 39.53 in							
Performance Specifications								
ΔIIC Sound Rating (ASTM E2179)	ΔIIC 18							
ΔLw Sound Rating (ISO 10140-3)	ΔLw 11 dB							
Slip Resistance (ASTM D2047)	>0.5 dry/wet required, ADA Compliant							
Bacteria Resistance (ASTM 2180/ASTM G21)	Resistant to bacteria, fungi and micro-organism activity							
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level							
Hardness (ASTM 2240)	Shore type A							
Static Load Limit (ASTM F970)	≤ 0.005 in with 250 lbs required, Passes @ 800 psi							
Rolling Load Limit (ASTM F2753)	≤ 850 lbs/sq in; for forklift traffic nora polyurethane adhesive is required							
Abrasion Resistance (ASTM D3389)	≤ 0.035 oz (1.0 g) required, Passes							
Resistance to Heat (ASTM F1514)	Passes							
Radiant Flux (ASTM E648)	Class 1							
Smoke Density (ASTM E662)	< 450							
Size & Squareness (ASTM F2055)	Passes							
Thickness (ASTM F386)	Passes							
Dimensional Stability (ASTM F2199)	Passes							
Resistance to Chemicals (ASTM F925)	Passes							
Resistance to Oil & Grease (ISO 26987)	Passes							
Static Generation (AATCC 134)	< 1000 Volts at 20% RH							
Thermal Transmission (ASTM C518)	R-value of -0.90							
Health + Environmental Specifications								
Embodied Carbon (Cradle to Gate)	14.1 kg CO ₂ /M ²							
Indoor Air Quality	Greenguard Gold							
Disclosure of Environmental Impacts	Environmental Product Declaration							
Disclosure of Product Ingredients	Health Product Declaration							
Environmental Certifications	Cradle to Cradle v3.1 Silver Greenhealth Approved PEFC Certified							
LEED	Contributes to multiple IEQ and MR Credits							
Technical Information								
Installation	nora Installation Guidelines							
Maintenance	Recommended nora Maintenance Guidelines							
Warranty	15 Year Standard Warranty							
Installation Method	Directional							
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.							

Manufacturing Location ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany

Downloads

nora Guide Spec	Download Guide Spec
-----------------	-------------------------------------

nora Flyer	Download Flyer
------------	--------------------------------

nora Viewbook	Download Viewbook
---------------	-----------------------------------
