



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** norament 920 stairtread **Color** Black **Collection** norament **Format** Stairtread  
**Surface** Round Pastille **Product Options** Standard **Thickness** 4.5mm

**Product Specifications**

Article Number	0465
Construction	Homogeneous Rubber Compound
Surface	Round Pastille
Format	Stairtread
Size	19.68 in x 50.59 in

**Performance Specifications**

Slip Resistance (ASTM D2047)	>0.5 dry/wet required, ADA Compliant
Bacteria Resistance (ASTM 2180/ASTM G21)	Resistant to bacteria, fungi and micro-organism activity
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level
Hardness (ASTM 2240)	Shore type A
Static Load Limit (ASTM F970)	≤ 0.005 in with 250 lbs required, Passes @ 800 psi
Rolling Load Limit (ASTM F2753)	≤ 850 lbs/sq in; for forklift traffic nora polyurethane adhesive is required
Abrasion Resistance (ASTM D3389)	≤ 0.035 oz (1.0 g) required, Passes
Resistance to Heat (ASTM F1514)	Passes
Radiant Flux (ASTM E648)	Class 1
Smoke Density (ASTM E662)	< 450
Tunnel Test (ASTM E84)	Class A
Size & Squareness (ASTM F2055)	Passes
Thickness (ASTM F386)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Resistance to Oil & Grease (ISO 26987)	Passes
Static Generation (AATCC 134)	< 1000 Volts at 20% RH

**Health + Environmental Specifications**

Indoor Air Quality	<a href="#">Greenguard Gold</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>

**Packaging**

Quantity per Piece	50.4 in (1285 mm)
Weight per Piece	8.9 lbs
Pieces per Pallet	75

**Technical Information**

Installation	<a href="#">nora Installation Guidelines</a>
Maintenance	<a href="#">Recommended nora Maintenance Guidelines</a>
Warranty	<a href="#">15 Year Standard Warranty</a>
Installation Method	Directional
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.

Manufacturing Location ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany

**Downloads**

nora Guide Spec	<a href="#">Download Guide Spec</a>
nora Flyer	N0042N
nora Viewbook	<a href="#">Download Viewbook</a>