



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** noraplan dariva **Color** Argan **Collection** noraplan **Format** Sheet **Surface** Smooth **Product Options** Standard **Thickness** 3.0mm

#### Product Specifications

Article Number	161F
Construction	Homogeneous Rubber Compound
Class	ASTM F1859 Standard Specification for Rubber Sheet Floor Covering without Backing
Surface	Smooth
Total Thickness	3 mm
Format	Sheet
Size	49.21 ft x 48 in

#### Performance Specifications

ΔIIC Sound Rating (ASTM E2179)	ΔIIC 13
ΔLw Sound Rating (ISO 10140-3)	ΔLw 10 dB
Slip Resistance (ASTM D2047)	>0.5 dry/wet required, ADA Compliant
Bacteria Resistance (ASTM 2180/ASTM G21)	Resistant to bacteria, fungi and micro-organism activity
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level
Hardness (ASTM 2240)	Shore type A
Static Load Limit (ASTM F970)	≤ 0.005 in with 250 lbs required, Passes @ 800 psi
Rolling Load Limit (ASTM F2753)	≤ 550 lbs/sq in; no forklift traffic
Abrasion Resistance (ASTM D3389)	≤ 0.035 oz (1.0 g) required, Passes
Resistance to Heat (ASTM F1514)	Passes
Radiant Flux (ASTM E648)	Class 1
Smoke Density (ASTM E662)	< 450
Thickness (ASTM F386)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Static Generation (AATCC 134)	< 1000 Volts at 20% RH
Thermal Transmission (ASTM C518)	R-value of 0.04

#### Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	6.69 kg CO <sub>2</sub> /M <sup>2</sup>
Biobased Content (ASTM D6866)	32%
Indoor Air Quality	<a href="#">Greenguard Gold</a>
Material Composition	PVC-free and also free of added Formaldehyde, Heavy Metal Stabilizers and Ortho Phthalates and Halogenated Flame Retardants
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	Cradle to Cradle v3.1 Silver Greenhealth Approved PEFC Certified
LEED	Contributes to multiple IEQ and MR Credits

#### Packaging

Quantity per Roll	157.58365 ft <sup>2</sup> (14.64 m <sup>2</sup> )
Weight per Roll	165.46 lbs
Rolls per Pallet	12

#### Technical Information

Installation	<a href="#">nora Installation Guidelines</a>
Maintenance	<a href="#">Recommended nora Maintenance Guidelines</a>
Warranty	<a href="#">15 Year Standard Warranty</a>
Installation Method	Directional

Wheel Types	No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A $\leq 90$
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.
Manufacturing Location	ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany

---

**Downloads**

nora Guide Spec	<a href="#">Download Guide Spec</a>
nora Flyer	<a href="#">Download Flyer</a>
nora Viewbook	<a href="#">Download Viewbook</a>