



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product noraplan environcare **Color** Car Wash **Collection** noraplan **Format** Sheet
Surface Smooth **Product Options** Standard **Thickness** 2.0mm

Product Specifications

Article Number	1462
Construction	Homogeneous Rubber Compound
Class	ASTM F1859 Standard Specification for Rubber Sheet Floor Covering without Backing
Surface	Smooth
Total Thickness	2 mm
Format	Sheet
Size	49.21 ft x 48 in

Performance Specifications

ΔIIC Sound Rating (ASTM E2179)	ΔIIC 12
ΔLw Sound Rating (ISO 10140-3)	ΔLw 8 dB
Slip Resistance (ASTM D2047)	>0.5 dry/wet required, ADA Compliant
Bacteria Resistance (ASTM 2180/ASTM G21)	Resistant to bacteria, fungi and micro-organism activity
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level
Hardness (ASTM 2240)	Shore type A
Static Load Limit (ASTM F970)	≤ 0.005 in with 250 lbs required, Passes @ 800 psi
Rolling Load Limit (ASTM F2753)	≤ 450 lbs/sq in; no forklift traffic
Abrasion Resistance (ASTM D3389)	≤ 0.035 oz (1.0 g) required, Passes
Resistance to Heat (ASTM F1514)	Passes
Radiant Flux (ASTM E648)	Class 1
Thickness (ASTM F386)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Static Generation (AATCC 134)	< 1000 Volts at 20% RH
Thermal Transmission (ASTM C518)	R-value of 0.04

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	4.44 kg CO ₂ /M ²
Biobased Content (ASTM D6866)	32%
Indoor Air Quality	Greenguard Gold
Material Composition	PVC-free and also free of added Formaldehyde, Heavy Metal Stabilizers and Ortho Phthalates and Halogenated Flame Retardants
Disclosure of Environmental Impacts	Environmental Product Declaration
Environmental Certifications	Cradle to Cradle v3.1 Silver Greenhealth Approved PEFC Certified
LEED	Contributes to multiple IEQ and MR Credits

Packaging

Quantity per Roll	196.9796 ft ² (18.3 m ²)
Weight per Roll	137.89 lbs
Rolls per Pallet	16

Technical Information

Installation	nora Installation Guidelines
Maintenance	Recommended nora Maintenance Guidelines
Warranty	15 Year Standard Warranty
Installation Method	Directional
Wheel Types	No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A ≤90
Storage	Store within a temperature range of -5°F (-21°C) to 120°F (49°C) under the following conditions: pallets must remain intact with sheet

goods standing on end, undamaged, and not stacked; goods must be in a permanently dry environment, with no direct sunlight. Adhesives and cold weld must remain at room temperature without freezing.

Manufacturing Location ISO 9001, 14001, and 50001 Certified Facility in Weinheim, Germany

Downloads

nora Guide Spec [Download Guide Spec](#)

nora Flyer [Download Flyer](#)

nora Viewbook [Download Viewbook](#)
