



## Semi-Transparent Alkyd/Oil Stain

## GENERAL DESCRIPTION

Protects wood from moisture and sun damage while adding a rich, beautiful color that enhances the wood grain. Fortified with **PENETROL®** for excellent penetration. Recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

## RECOMMENDED SUBSTRATES

Wood Decks	Wood Railings
Wood Fences	Wood Siding
Wood Outdoor Furniture	Wood Trim

## PRODUCT INFORMATION

FLD802 Neutral Base\*

\*Must be tinted. Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

## PACKAGING

1 - Gallon (3.78 L)  
5 - Gallon (18.9 L)

## FEATURES / BENEFITS

## Features

Solventborne Alkyd Formulation

Fortified with **PENETROL** Additive

Added Mildewcide Package

Water Resistant Coating

## PRODUCT DATA

**PRODUCT TYPE:** Alkyd-Oil  
**VOLUME SOLIDS:** 32% +/- 2%  
**WEIGHT SOLIDS:** 38% +/- 2%  
**WEIGHT/GALLON:** 7.1 lbs. (3.2 kg) +/- 0.2 lbs. (91 g)  
**VOC:** < 550 g/L (4.6 lbs./gal.)

**COVERAGE:** Approximately 250 to 350 sq. ft. (23 to 33 sq. meters) per gallon (3.78 L) depending on application, wood texture, and porosity.

**DRYING TIME:** Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

## PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material: 50 to 90°F (10 to 32°C)  
Ambient: 50 to 90°F (10 to 32°C)  
Substrate: 50 to 90°F (10 to 32°C)

**CLEANUP:** Clean brushes and tools with mineral spirits. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH FLOOD SEMI-TRANSPARENT ALKYD/OIL STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.**

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** 108°F (42°C)

## Benefits

Provides a rich, subtle and fade resistant color while providing protection against damage from UV rays.

Provides excellent penetration.

Provides a mildew resistant finish

Protects wood from water damage.

## Semi-Transparent Alkyd/Oil Stain

## GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying stain. After rinsing, allow wood to dry. Sand all cleaned wood using 80-120 grit sandpaper for vertical surfaces and 60-80 grit sandpaper for horizontal surfaces. Always sand in direction of the wood grain and remove sanding dust. Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 sec. to 2 min., depending on climate, the surface is ready for staining.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**NEW WOOD and PRESSURE TREATED LUMBER:** Mill glaze must be removed by sanding and wood must pass water absorption test.

## APPLICATION INFORMATION

Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. DO NOT THIN. Intermix containers to ensure color uniformity. Stir thoroughly and often during use. Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration. Apply one thin coat with a high-quality brush, roller, paint/stain pad, or with spray equipment. When applying by roller or spray, always back-brush for best results. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge. Heavy application can cause uneven appearance and may increase dry time depending on conditions.

**Application Equipment:** High-quality natural bristle brush, roller, paint/stain pad, pump-up sprayer or airless sprayer. Airless spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

**Thinning:** Do Not Thin

## LIMITATIONS OF USE

FOR EXTERIOR USE ONLY. FOR WOOD SUBSTRATES ONLY. While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

## PRECAUTIONS

For warning information, please refer to the SDS and label. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2025 The Pittsburgh Paints Co. All Rights Reserved. *Flood*, *Flood and Paintbrush Design*, and *Penetrol* are registered trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



The Pittsburgh Paints Co.  
400 Bertha Lamme Drive  
Cranberry Township, PA 16066  
[www.flood.com](http://www.flood.com)

Technical Service  
1-800-441-9695

FLD802 6/2025