

## 1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Tarkett Contour Series Wood Stone Luxury vinyl floor covering with Techtonic™ protection to deliver unmatched durability in high-traffic areas in a plank design.
- 1.2. **Manufacturer:**  
Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)
- 1.3. **Proprietary Product Description:**
- 1.4.1. **Construction:** Tarkett Contour is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 32-mil wear layer and state-of-the-art Techtonic™ protective finish for long term performance. Tarkett's Techtonic™ is a massive shift forward in performance for hard surface floors. Its advanced polyurethane technology is super tough, resisting scratching, abrasions, scuffing and staining.

### 1.3.1. Styles & Physical Characteristics:

Contour Series (See below for standard embossing, sizing availability, and packaging info)

- **Finish:** Techtonic™
- **Wear layer Thickness:** 32 mil (0.8 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** .120" (3 mm)

## 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Flexibility** (ASTM F137): Passes
- 2.3. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$   
**\*Modified 2000 psi:**  $\leq 0.005''$
- 2.4. **Residual Indentation** (ASTM F1914): Passes
- 2.5. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$  SCOF
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.8. **Resistance to Light** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Fire Performance, Critical Radiant Flux** (ASTM E648): Class 1 ( $> 0.45$  W/cm<sup>2</sup>)
- 2.11. **CAN/ULC S102.2:** FSV 120 / SDV 455

## 3. INSTALLATION

See Contour Luxury Vinyl Plank installation instructions for complete details.

### 3.1 Adhesives:

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959HM High Moisture Substrate Adhesive**  
Porous Substrate: 125-150 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour Maintenance Instructions for complete maintenance details.

## 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
Contact Technical support at (800)-899-8916 or Email: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

## 7. WARRANTY

Limited 25-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)

\* Static loads greater than 250 psi fall outside of the scope of the ASTM F970 Test Method. Modified static load testing does not provide information related to the long-term exposure and the residual indentation of an installed floorcovering system which includes the subfloor, adhesive, underlayment, and cementitious patching/leveling compounds. Residual indentation(s) may remain visible in any resilient flooring installation, however, overhead lighting, natural lighting and the application of a gloss floor finish may increase the appearance.

<b>ABSTRACT:</b> 18x18, 36x36 – Quarter Turn, Vertical Ashlar, Horizontal Ashlar 9x36, 12x36 – Vertical Ashlar 6x36, 6x24 – Herringbone, Unidirectional 18x36 – Vertical Ashlar	<b>STANDARD EMBOSS</b>	<b>SIZES AVAILABLE</b>					
		6x36	9x36	12x36	18x18	18x36	36x36
<b>Collaborative:</b> Create Clarity (PCCT), Create Emphasis (PCCA), Create Expression (PCCP), Create Meaning (PCCS), Create Together (PCCM)	Quarry			•	•		
<b>Mindful Maker:</b> Aquarelle (PCQL), Demure (PCDE), Needle & Thread (PCNT)	Quarry			•	•		
Method (PCMH)	Quarry		•				
PM Square (PCPM)	Quarry				•		
<b>Color Play:</b> Color Beam (PCBE), Color Pop (PCOP), Color Weave (PCWE)	Quarry	•	•		•		
Analog Field (PCAO)	Quarry			•	•		
Aura (PCAU)	Quarry		•		•		
Broadcloth (PCBC)	Quarry				•		
CeraMix (PCCX)	Quarry	•					
Chenille (PCCH)	Quarry	•			•		
Crafted Cane (PCCC)	Quarry	•		•			
Drop Cloth (PCDC)	Quarry		•		•		
Entwine (PCEN)	Quarry		•				
Factor (PCFC)	Quarry	•			•		
Faux Bois (PCFB)	Tick	•	•				
Felt (PIFE)	Quarry	•			•	•	
Fiber Effect (PCFT)	Quarry		•		•		
Filament (PCFI)	Tick		•	•	•		
Foil (PIFO)	Quarry	•			•	•	
Foliate (PCFO)	Quarry		•		•		
GeoGrid (PCGE):	Pathway	•		•	•	•	•
Glint (PCGI)	Quarry			•			
Illusion (PCIN):	Quarry		•	•	•		
Marble (PIMA)	Quarry	•			•	•	
Meshwork (PCGF)	Quarry			•	•		
Mindset (PCMM)	Quarry			•	•		
Mirage (PCMI)	Quarry		•		•		
Outliners (PCOU)	Quarry	•	•		•		
PM Square (PCPM)	Quarry				•		
Polyomino (PCPY)	Quarry			•	•		
Ribweave (PIRI)	Quarry	•			•	•	
Riverbend (PCRB)	Quarry			•	•		
Substrate (PCSU):	Quarry		•	•	•		
Texterran (PCTE)	Quarry		•		•		
Woven Reed (PCWR):	Quarry	•			•		

## Tarkett North America

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)

<b>WOOD:</b> 4x36, 6x24, 6x36, 6x48, 7.2x48 – Herringbone, Unidirectional 9x36 – Vertical Ashlar Hexagon, Triangle - Random	EMBOSSING					
	Frost (FR)	Natural Grain (NG)	Quarry (QU)	Rough Grain (RG)	Sawn (STDW)	Tick (TK)
<b>Antique Wood (PCAN)</b> 4x36, 6x36, 6x48, 6x24, Hexagon, Triangle			STD			
3815, 3816						
3810, 3811					STD	
<b>Modern Wood (PCMD)</b> 4x36, 6x36, 6x48, 6x24, Hexagon, Triangle				STD		
All colors						
<b>Spalted (PCSP)</b> 6x36, 9x36, 6x48, 7.2x48, 6x24, Hexagon, Triangle		STD				
All Colors						
<b>True To Form Woods:</b> Artful Oak (PCMK), Branched Oak (PCBR), Chronical Oak (PCCL), French Oak (PCFH), Medley Maple (PCEM), Natural Walnut (PCWT), Proper Oak (PCPO), Wetland Cypress (PCCY) 6x36, 6x48, 6x24, Hexagon, Triangle				STD		
<b>French Oak (PCFH)</b>						STD
All Other Colors						
<b>True To Form: Wildcraft Maple (PCWC)</b> 6x36, 6x48, 6x24, Hexagon, Triangle		STD				
All Colors						
<b>Townhall (PCTH)</b> 6x36, 9x36, 6x48, 7.2x48, 6x24, Hexagon, Triangle				STD		
All Colors						
<b>Wildwood (PCWD)</b> 6x36, 7.2x48, 12x36, 6x24, Hexagon, Triangle				STD		
All Colors						

<b>STONE:</b> 18x18, 36x36 – Horizontal Ashlar, Quarter Turn, Vertical Ashlar 12x24, 12x36, 9x36 – Vertical Ashlar 6x36, 6x24 – Herringbone, Unidirectional Hexagon, Triangle – Random	EMBOSSING			
	Fresco (FC)	Frost (FR)	Pathway (PH)	Quarry (QU)
<b>Arterra (PCAT)</b> 6x36, 6x24, Hexagon, Triangle				STD
<b>Artifice (PCAR)</b> 18x18, 12x36, 6x24, Hexagon, Triangle				STD
<b>Carrera &amp; Carrera Accent (PCRA)</b> 18x18, 12x36, 6x24, Hexagon, Triangle				STD
<b>Metamorphic (PCMP)</b> 9x36, 6x24, Hexagon, Triangle				STD
<b>Modern Stone (PCMS)</b> 12x24, 18x18, 6x24, Hexagon, Triangle				STD
<b>Parisian (PCPR)</b> 18x18, 12x36, 6x24, Hexagon, Triangle				STD
<b>Passageway (PCPA)</b> 18x18, 6x24, Hexagon, Triangle			STD	
<b>Rust Rings (PCRR)</b> 18x18, 6x36, 12x36, 18x36, 36x36, 6x24, Hexagon, Triangle			STD	
<b>Solstice (PCSO)</b> 18x18, 6x36, 12x36, 18x36, 36x36, 6x24, Hexagon, Triangle			STD	
<b>True To Form Stone:</b> Castlerock Sandstone (PCSN), Ebbing Travertine (PCET), Melded Concrete (PCMC), Mineral Basalt (PCMB), Native Soapstone (PCAV), Palladian (PCPD) 6x36, 12x36, 18x18, 6x24, Hexagon, Triangle				STD

Appropriate surface texture, pattern, and color play a significant role in LVT performance, wear, and maintenance requirements. Please consult your account executive to determine the emboss that will best fit the design and performance goals for your project.

## Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)

© 2026 Tarkett USA Inc. 01/2026

**PACKAGING INFORMATION:**

	Size	Pcs Per Carton	Sqft. Per Carton	Lbs. Per Carton	Cartons Per Pallet
Tile	12" x 12" (30.48 x 30.48 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	54
	12" x 18" (30.48 x 45.72 cm)	30	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	12" x 24" (30.48 x 60.96 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	12" x 36" (30.48 x 91.44 cm)	15	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	18" x 18" (45.72 x 45.72 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	18" x 36" (45.72 x 91.44 cm)	10	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	9" x 36" (22.86 x 91.44 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	36" x 36" (91.44 x 91.44 cm)	10	90 (8.4 m <sup>2</sup> )	90 (40.8 kg)	20
Planks	4" x 36" (10.16 x 91.44 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	6" x 36" (15.24 x 91.44 cm)	24	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	66
	6" x 48" (15.24 x 121.92 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	7.2" x 48" (18.29 x 121.92 cm)	15	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	60
Hexagon	12" x 13.8" (30.48 x 35.05 cm)	20	17.3 (1.61 m <sup>2</sup> )	17.3 (7.8 kg)	52
Triangle	6.9" (17.5 cm)	120	17.32 (1.61 m <sup>2</sup> )	17.3 (7.8 kg)	52

**Tarkett North America**

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)