

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Event⁺ Series Luxury vinyl floor covering with Techtonic™ coating that delivers extreme durability and ease of maintenance in high traffic environments. Suitable for commercial working environments and office.

1.2. Manufacturer:

Tarkett North America Phone (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com
E-mail: info@tarkett.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Event⁺ Series is constructed with 30 mil wear layer reinforced with a Techtonic finish in numerous wood and stone patterns to provide an affordable, natural looking flooring that is stocked for faster turnaround times.

1.3.2. Styles:

(See below for standard embossing, sizing availability, and packaging info)

- **Finish:** Techtonic
- **Wear layer thickness:** 30 mil (0.76 mm)
- **Edge treatment:** Square Edge (SE)
- **Overall thickness:** 0.120" (3.0 mm)
- 32 Wood / 24 Stone patterns

2. PERFORMANCE AND TECHNICAL DATA

- 2.1 Meets ASTM F1700, Class III, Type B performance
- 2.2 **Static Load Limit** (ASTM F970): 250 psi, $\leq 0.005''$
***Modified 2000 psi:** $\leq 0.005''$
- 2.3 **Residual Indentation** (ASTM F1914): Passes
- 2.4 **Static Coefficient of Friction** (ASTM D2047): SCOF ≥ 0.5
- 2.5 **Dimensional Stability** (ASTM F2199): Passes
- 2.6 **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.7 **Resistance to Light** (ASTM F1515): $\Delta\Sigma \leq 8.0$
- 2.8 **Chemical Resistance** (ASTM F925): Passes
- 2.9 **Fire Resistance** (ASTM E648): CRF ≥ 0.45 watts/cm² NFPA, Class I
- 2.10 **CAN/ULC S102.2:** FSV 105 / SDV 340

3. INSTALLATION

3.1 See Tarkett Luxury Vinyl Plank installation instructions for complete details.

3.2 Adhesives:

- **Tarkett RollSmart Adhesive:**
Coverage: 350 – 400 sq. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959HM High Moisture Substrate Adhesive**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour/Event/Latitude/Resolve Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 20-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com

* Static loads greater than 250 psi fall outside of the scope of the ASTM F970 Test Method. Modified static load testing does not provide information related to the long-term exposure and the residual indentation of an installed floorcovering system which includes the subfloor, adhesive, underlayment, and cementitious patching/leveling compounds. Residual indentation(s) may remain visible in any resilient flooring installation, however, overhead lighting, natural lighting and the application of a gloss floor finish may increase the appearance.

STANDARD EMBOSSING AND SIZE AVAILABILITY:

Woods Installation Methods:

6x36, 6x48 – Herringbone, Unidirectional

Stones Installation Methods:

18x18, 36x36 – Vertical Ashlar, Horizontal Ashlar, Quarter-Turn

12x24 – Vertical Ashlar

Abstract Installation Methods:

18x18 – Vertical Ashlar, Horizontal Ashlar, Quarter-Turn

12x24 – Vertical Ashlar

WOOD	Natural Grain (NG)	Third Grain (TG)	Rustic (RU)
Classic Plank (PECK) 6x36			
3305, 3307, 3308, 3309	STD		
3321		STD	
Classic Plank (PECK) 6x48			
11223	STD		
Crafted Plank (PECF) 6x48			
All colors <i>except 11212, 11213</i>	STD		
11212, 11213		STD	
Heritage Plank (PEHP) 6x36			
3350, 3354			STD
GW29		STD	
GW38	STD		
Heritage Plank (PEHP) 6x48			
11219, 11220, 11221, 11222			STD

ABSTRACTS	Frost (FR)	Quarry (QU)
Melange (PEME) 18x18		
All colors		STD
Texterran (PETE) 12x24		
All colors	STD	

STONE	Frost (FR)	Rock (RK)	Quarry (QU)
Travertine (PETR) 18x18			
7211			STD
Travertine (PETR) 12x24			
11195	STD		
Slate (PESL) 12x24			
All colors		STD	
Urban Stone (PEUS) 18x18			
2100, 2101, 2104, 2105		STD	
Urban Stone (PEUS) 12x24			
11199, 11200, 11201, 11202, 11203			STD
Urban Stone (PEUS) 36x36			
11204, 11205, 11206			STD
Quartzite (PEQZ) 18x18			
All colors			STD

PACKAGING INFORMATION:

	Size	Pcs Per Carton	Sqft. Per Carton	Lbs. Per Carton	Cartons Per Pallet
Tile	12" x 24" (30.48 x 60.96 cm)	18	36 (3.3 m ²)	37.17 (16.9 kg)	72
	18" x 18" (45.72 x 45.72 cm)	20	45 (4.2 m ²)	47.97 (21.8 kg)	48
	36" x 36" (91.44 x 91.44 cm)	6	54 (5.0 m ²)	62.58 (28.4 kg)	28
Plank	6" x 36" (15.24 x 91.44 cm)	24	36 (3.3 m ²)	37.85 (17.2 kg)	60
	6" x 48" (15.24 x 121.92 cm)	18	36 (3.3 m ²)	39.15 (17.8 kg)	72

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkett.com

© 2026 Tarkett USA Inc. 01/2026