



## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Victory Series Luxury vinyl floor covering is homogeneous, hand-made vinyl tile made in Florence, Alabama, USA. Also available for custom ultrasonic cut floor designs created by Tarkett Imaginations™ team using CAD technology.

### 1.2. Manufacturer:

Tarkett North America      Phone (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)  
E-mail: [info@tarkett.com](mailto:info@tarkett.com)

### 1.3. Proprietary Product Description:

1.3.1. **Construction:** Victory Series made with Phthalate-free, virgin vinyl and metallic pigments, hand-crafted for unique effects on every tile.

### 1.3.2. Styles & Physical Characteristics:

(See table for packaging info)

- **Hues & Tones (VCR)**
- **Mineral Chip (VMN)**
- **Wear layer thickness:** n/a (homogenous product)
- **Edge treatment:** Square Edge (SE) or Slight Bevel (SB)
- **Overall thickness:** 0.120" (3.0 mm)
- **Standard Emboss:** Slate (SS) (Granite [JS] available)

## 2. PERFORMANCE AND TECHNICAL DATA

- 2.1 Meets ASTM F1700, Class I, Type B performance
- 2.2 **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$   
**\*Modified 1500 psi:**  $\leq 0.005''$
- 2.3 **Residual Indentation** (ASTM F1914): Passes
- 2.4 **Static Coefficient of Friction** (ASTM D2047): SCOF  $\geq 0.5$
- 2.5 **Dimensional Stability** (ASTM F2199): Passes
- 2.6 **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.7 **Resistance to Light** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.8 **Chemical Resistance** (ASTM F925): Passes
- 2.9 **Fire Resistance** (ASTM E648): CRF  $\geq 0.45$  watts/cm<sup>2</sup> NFPA, Class I
- 2.10 **CAN/ULC S102.2:** FSR 85 / SDC 325

## 3. INSTALLATION

3.1 See Tarkett Victory Solid Vinyl Tile installation instructions for complete details.

**NOTE: Due to the unique process in the manufacturing of this tile, Victory Tile can be affected by extended storage periods in warehouse environments. Victory Tile is made to order and intended for installation within 6 months of delivery.**

### 3.2 Adhesives:

- **CENTI 2001 Wet Set**  
Porous ONLY: 125-150 sq. ft. per gallon
- **CENTI 2000 Epoxy**  
Porous & Non-porous: 125-150 sq. ft. per gallon

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour/Event/Latitude/Resolve Maintenance Instructions for complete maintenance details.

## 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical Support at (800) 899-8916 or E-mail: [Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

## 7. LIMITED WARRANTY

Limited 20-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)

\* Static loads greater than 250 psi fall outside of the scope of the ASTM F970 Test Method. Modified static load testing does not provide information related to the long-term exposure and the residual indentation of an installed floorcovering system which includes the subfloor, adhesive, underlayment, and cementitious patching/leveling compounds. Residual indentation(s) may remain visible in any resilient flooring installation, however, overhead lighting, natural lighting and the application of a gloss floor finish may increase the appearance.

## STANDARD EMBOSSING & SIZING AVAILABILITY

Embossing:

- **Hues & Tones:** Slate (SS)
- **Mineral Chip:** Granite (JS)

Sizing:

- **Hues & Tones**
  - 18x18 – Quarter Turn, Horizontal Ashlar, Vertical Ashlar
  - 6x36 – Unidirectional, herringbone
  - 12x36 – Vertical Ashlar
  - 36x36 – Quarter Turn, Horizontal Ashlar, Vertical Ashlar
- **Mineral Chip**
  - 18x18 – Quarter Turn, Horizontal Ashlar, Vertical Ashlar
  - 6x36 – Unidirectional, herringbone
  - 12x36 – Vertical Ashlar

## PACKAGING INFORMATION:

	Size	Pcs Per Carton	Sqft. Per Carton	Lbs. Per Carton	Cartons Per Pallet
Tile	12" x 36" (30.48 x 91.44 cm)	15	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	18" x 18" (45.72 x 45.72 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	36" x 36" (91.44 x 91.44 cm) (Not available for Mineral Chip)	10	90 (8.4 m <sup>2</sup> )	90 (40.8 kg)	20
Planks	6" x 36" (15.24 x 91.44 cm)	24	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	66

---

### Tarkett North America

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)