



1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Masquerade

1.2. Manufacturer:

Tarkett North America Phone: (800) 899-8916  
 30000 Aurora Rd. (440) 543-8916  
 Solon, Ohio 44139  
 Web: www.tarkett.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Masquerade is manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861 Standard Specification for Resilient Wall Base, Type TP, and Group 2.

1.3.2. Styles & Physical Characteristics (Wallbase):

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
<b>Classic</b> (MW-XX-Z)	3/8" x 5 1/4" x 8' (9.5mm x 13.3cm x 2.44m)	6	48 (14.6m)	61.8 (28.0 kg)
<b>Exhibit</b> (MW XX FS)	1/4" x 4 1/4" x 8' (6.35mm x 10.8cm x 2.44m)	8	64 (19.5m)	46.5 (21.1 kg)
<b>Exhibit 6"</b> (MW-XX-FS6)	1/4" x 6" x 8' (6.35mm x 15.24cm x 2.44m)	8	64 (19.5m)	61 (27.7 kg)
<b>Exhibit 8"</b> (MW-XX-FS8)	1/4" x 8" x 8' (6.35mm x 20.32 cm x 2.44m)	4	32 (9.8m)	44 (20.0 kg)
<b>Ledge</b> (MW-XX-X62)	0.35" x 6" x 8' (8.89mm x 15.24cm x 2.44m)	5	40 (12.2m)	58 (26.3 kg)
<b>Oblique</b> (MW-XX-N)	3/8" x 3" x 8' (9.52mm x 7.62cm x 2.44m)	7	56 (17.1 m)	41.1 (18.6 kg)
<b>Outline</b> (MW-XX-D)	5/16" x 3 1/2" x 8' (7.94mm x 8.89cm x 2.44m)	10	80 (24.4 m)	46 (20.9 kg)
<b>Reveal</b> (MW-XX-F)	1/4" x 4 1/4" x 8' (6.35mm x 10.8cm x 2.44m)	8	64 (19.5m)	49.7 (22.5 kg)
<b>Reveal 6"</b> (MW XX F6)	1/4" X 6" X 8' (6.35mm x 15.2cm x 2.44m)	8	64 (19.5m)	66 (29.9 kg)
<b>Reveal 8"</b> (MW XX F8)	1/4" x 8" x 8' (6.35mm x 20.3cm x 2.44m)	4	32 (9.8 m)	47.8 (21.7 kg)
<b>Silhouette</b> (MW-XX-J)	1/2" x 4" x 8' (12.7mm x 10.16cm x 2.44m)	6	48 (14.6m)	39.3 (17.8 kg)
<b>Stance</b> (MW-XX-X60)	0.35" x 4 1/2" x 8' (8.89mm x 11.43cm x 2.44m)	5	40 (12.2m)	33 (15.0 kg)
<b>Stance 6"</b> (MW-XX-X61)	0.35" x 6" x 8' (8.89mm x 15.24cm x 2.44m)	5	40 (12.2m)	45 (20.4 kg)
<b>Traditional</b> (MB XX)	0.125" x 4" x 4' (3.17mm x 10.16cm x 1.22m)	30	120 (36.6m)	41 (18.6 kg)

1.3.3. Physical Characteristics (Quarter Round/Shoe Moulding):

Style	Dimension	Per Carton		
		Pcs.	LF	Lbs.
<b>1/2" Quarter Round</b> (QTR-XX-A)	1/2" wide x 1/2" radius x 8' (12.7mm x 12.7mm x 2.44m) With pre-applied, pressure sensitive adhesive backing	20	160 (48.8 m)	25 (11.3 kg)
<b>3/4" Quarter Round</b> (QTR-XX-D)	3/4" wide x 3/4" radius x 8' (19.05mm x 19.05mm x 2.44m) With pre-applied, pressure sensitive adhesive backing	10	80 (24.4 m)	27 (12.2 kg)
<b>Shoe Mold</b> (SHU-XX-A)	1/4" wide x 1 1/2" x 8' (6.35mm x 3.81cm x 2.44m) With pre-applied, pressure sensitive adhesive backing	10	80 (24.4 m)	19 (8.6 kg)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Products meet the following performance criteria for resistance to light, chemicals, and staining of adjacent materials when tested to the methods as described in ASTM F1861.
- Chemical resistance** (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution
- Resistance to light** (ASTM F 1515): ΔE < 8
- Fire Resistance:**  
ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I
- CAN/ULC-S102.2:** FSR 48 / SDV 366

3. AVAILABILITY AND COST

For availability and cost contact authorized Tarkett distributors nationwide.

4. INSTALLATION

- See Tarkett Masquerade installation instructions for complete details.
- Adhesives:**  
Quarter Round (QTR XX A, QTR XX D) and Shoe Molding (SHU XX A) are self-stick accessories designed for application to Tarkett Millwork and do not require additional adhesives.

Tarkett North America

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
 info@tarkettna.com

www.tarkett.com



• **Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)**

Application: Brush or roller

Approximate coverage:

Base Height	1 qt. unit: (0.95 L)		1 gal. unit: (3.79 L)	
	Lf.	M.	Lf.	M.
3"	96-144	29-44	576-860	176-262
3 ½"	81-123	25-38	493-736	150-224
4"	72-108	22-33	432-646	132-197
4 ¼"	68-102	21-31	407-607	124-185
5 ¼"	55-82	17-25	329-491	100-150
6"	48-58	15-18	192-230	59-70
8"	36-43	11-13	144-173	44-53

• **Tarkett 960 Cove Base Adhesive (Porous surfaces)**

Application: 1/8x1/8x1/8 Square or V-notch trowel

Approximate Coverage:

Base Height	1/8" Square Notch Coverage per Gal. (3.79 L.)		1/8" V- Notch Coverage per Gal. (3.79 L.)	
	Lf.	M.	Lf.	M.
3"	275-325	83.8-99	300-350	91.4-106.7
3.5"	230-280	70.1-85.3	275-325	83.8-99
4"	200-250	61-76.2	250-300	76.2-91.4
4 ¼"	185-235	56.4-71.6	225-275	68.6-83.8
5 ¼"	145-195	44.2-59.4	165-205	50.3-62.5
6"	100-150	30.5-45.7	140-180	42.7-54.9
8"	100-125	30.5-38.1	110-140	33.5-42.7

5. **MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.

6. **TECHNICAL SERVICES**

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)

Contact Technical Support at (800) 899-8916 or E-mail:

[Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. **WARRANTY**

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**Tarkett North America**

Technical Services Department  
 30000 Aurora Road  
 Solon, Ohio 44139  
 800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)