

Specifications
Broken Stripe
by Alexander Girard, 1952
300091

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: 18 1/4" V, 52" H

(46cm V, 132cm H)

Bolt Size: 30 yards (27 m)

Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Contact your sales representative for pricing.

Maintenance

W-Clean with water-based cleanser.

**Testing**

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered*

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Broken Stripe

by Alexander Girard, 1952

300091

Environmental

- Greenguard Gold Certified
- LBC Red List Free
- REACH Compliant
- Contains Bio-Based Content
- FR Free
- Free of Intentionally Added PFAS

Warranty

3 years.

© 2021 Girard Studio, LLC, Maharam under license

Complete product information at maharam.com

800.645.3943



001 Ochre and Blue Gray Light



002 Emerald and Turquoise Light



003 Gray Violet and Viridian Light



004 Pink and Orange Light



005 Crimson and Orange



006 Peach and Raw Umber



007 Crimson White and Yellow Light



008 Violet and Navy



009 Madder Brown and Sepia