Maintenance Guidelines
Tilde
511501

maharam

Regular Maintenance
Using mild soap or detergent, machine wash on synthetic setting with a high water level and mild agitation. Temperature should not exceed 160°F. Extract gently. Wash with like materials.

If necessary, machine wash with a diluted bleach solution. This textile may also be spot cleaned with a diluted bleach solution as long as the bleach solution is rinsed thoroughly after application. If bleach is used without adequate rinsing, degradation to the textile will occur.

Air, cabinet, or tumble dry at a low temperature. Do not exceed 3-5 minutes on a synthetic cycle at a maximum of 140°F. Hang or fold immediately after drying.

Hand Iron
Iron at low heat setting (275°F) with a damp press cloth or steam iron with a dry press cloth.

Grid Head Press
Press for short intervals with minimum steam. Do not lock head.

Flat Bed Press
Press dampened drapery using cloth covering.

Avoid prolonged contact with heat.

Notes
The information above is a guide to help in the maintenance of Maharam textiles. Maharam can neither guarantee, nor take responsibility for specific results.

Under no circumstances shall Maharam be liable for any incidental, consequential, or other damage resulting from negligence, misuse, mishandling, or exposure of any chemicals used in connection with maintenance. Information relating to chemicals/cleaning solvents, environmental use, and human exposure should be reviewed with appropriate suppliers. All label instructions on their use and precautions should be followed.

07.25

maharam

Approved Cleaners

The Clorox Company
Clorox Healthcare Fuzion Cleaner Disinfectant

Various
1:10 Solution of Diluted Household Bleach

07.25