

# LED-Mirror Collection



DESIGN

SUSTAINABLE

DURABLE

BOBRICK



Bobrick's LED Mirror Collection brings high quality LEDs together with commercial grade mirror construction to provide a product that reflects quality, value and style.



B-164 Series



B-167 Series



B-167.MBLK

## STANDARD SIZES & STYLES:

### B-164 MIRRORS

| OVERALL SIZE |              |               |        |         |
|--------------|--------------|---------------|--------|---------|
| MODEL NO.    | W            | H             | Lumens | Wattage |
| B-164 1830   | 18" (460 mm) | 30" (762 mm)  | 2,100  | 19      |
| B-164 2436   | 24" (610 mm) | 36" (914 mm)  | 2,640  | 24      |
| B-164 2442   | 24" (610 mm) | 42" (1067 mm) | 2,900  | 26      |
| B-164 2739   | 27" (686 mm) | 39" (990 mm)  | 2,900  | 26      |

### B-167 MIRRORS

| OVERALL SIZE |                     |                    |        |         |
|--------------|---------------------|--------------------|--------|---------|
| MODEL NO.    | W                   | H                  | Lumens | Wattage |
| B-167 1844   | 18-1/8" (460 mm)    | 44-1/8" (1120 mm)  | 2,830  | 25      |
| B-167 2436   | 23-5/8" (600 mm)    | 35-3/8" (900 mm)   | 2,760  | 24      |
| B-167 2448   | 23-5/8" (600 mm)    | 47-2/8" (1200 mm)  | 3,310  | 29      |
| B-167 2632   | 25-19/32" (650 mm)  | 31-1/2" (800 mm)   | 2,650  | 23      |
| B-167 2739   | 27-9/16" (700 mm)   | 39-3/8" (1000 mm)  | 3,030  | 26      |
| B-167 5442   | 53-1/8" (1350 mm)   | 41-3/8" (1050 mm)  | 4,400  | 38      |
| B-167 5626   | 55-1/8" (1400 mm)   | 25-19/32" (650 mm) | 3,750  | 33      |
| B-167 6642   | 64-15/16" (1650 mm) | 41-3/8" (1050 mm)  | 4,965  | 46      |

Mirrors can be installed vertically or horizontally.

### NEW

### B-167.MBLK MIRRORS

| OVERALL SIZE    |              |              |        |         |
|-----------------|--------------|--------------|--------|---------|
| MODEL NO.       | W            | H            | Lumens | Wattage |
| B-167 2436.MBLK | 24" (610 mm) | 36" (914 mm) | 2,700  | 34      |





## STANDARD SIZES & STYLES:

**NEW**

### B-104.MBLK MIRRORS

#### OVERALL SIZE

| MODEL NO.       | W            | H             | Lumens | Wattage |
|-----------------|--------------|---------------|--------|---------|
| B-104 2448.MBLK | 24" (610 mm) | 48" (1220 mm) | 2,900  | 35      |



B-104.MBLK


### B-168 MIRRORS

#### OVERALL SIZE

| MODEL NO.  | W            | H            | Lumens | Wattage |
|------------|--------------|--------------|--------|---------|
| B-168 2739 | 27" (686 mm) | 39" (990 mm) | 2,500  | 26      |



B-168 Series



B-169 Series

### B-169 MIRRORS

#### OVERALL SIZE

| MODEL NO.  | W            | H                  | Lumens | Wattage |
|------------|--------------|--------------------|--------|---------|
| B-169 2436 | 24" (610 mm) | 36" (914 mm)       | 1,250  | 12      |
| B-169 2448 | 24" (610 mm) | 47-7/12" (1209 mm) | 1,500  | 14      |
| B-169 3040 | 30" (762 mm) | 40" (1016 mm)      | 1,450  | 14      |

Special order sizes available.

Contact Bobrick for information: [customerservice@bobrick.com](mailto:customerservice@bobrick.com)





## FEATURES & BENEFITS

| COMPETITIVE FEATURES                   | BOBRICK                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| <b>UL- Certification</b>               | Certified as required by UL as a complete unit under UL-962 (lighted furnishing)            |
| <b>Safety Against Glass-Breakage</b>   | High safety via PVC-film-backed glass, required by UL (962)                                 |
| <b>AC-Connection (110-277 Volt)</b>    | Two UL-certified or ETL-certified options; hard wiring and plugged (Optional; Order 164-57) |
| <b>Glass Thickness</b>                 | 5 mm                                                                                        |
| <b>Scratch Resistant</b>               | Gen 3 glass has high scratch resistance, also withstands salt spray test 4 times longer.    |
| <b>CRI* Overall Light Quality</b>      | 90+ (excellent)                                                                             |
| <b>Warm Light Quality, 3000 Kelvin</b> | Standard                                                                                    |
| <b>Light/Power Efficacy</b>            | 100+ Lumens/Watt (super efficient)                                                          |
| <b>IP Rating</b>                       | IP44 rated, suitability for damp commercial locations including resistance against solids   |
| <b>Sustainability</b>                  | Eco-friendly lead-free silver backing                                                       |
| <b>Dimming Option</b>                  | Standard                                                                                    |

\*CRI Color Rendering Index - how accurately the mirror can produce a light that matches a naturally referenced light source, such as the sun.



**BUILDING VALUE SINCE 1906**

**Customer Service:** 818-982-9600  
**Email:** customerservice@bobrick.com