360° PAINTED GRID

Suspension System

360° Painted Grid System with Axiom® Classic Perimeter Trim

This 9/16" and 15/16" profile suspension system is used to define open plenum spaces, or used as decorative accent on clouds and canopies.

KEY SELECTION ATTRIBUTES

- Helps to define space in an open/exposed plenum concept
- Available in Suprafine® 9/16" and Prelude® 15/16" profiles
- PeakForm® profile increases strength and stability for improved performance during installation
- 360 Pre-qualified colors are part of the Sustain portfolio
- Engineered without rotary stitching to maintain a streamlined visual profile
- SuperLock™ main beam clip is engineered for a strong, secure connection and fast, accurate alignment confirmed with an audible click; easy to remove/relocate
- Hot-dipped galvanized coating inhibits red rust better than electrogalvanized or painted systems
- Choice of matte and gloss finishes**
- XL® staked-on end detail provides secure locked connection; easy to remove, reuse, and relocate
- All acoustical grid and Axiom trim accessories (a.k.a. clips) are supplied as unpainted items. Exposed clips will need to be field painted after installation, if required for the project. See design considerations below for more information.
- 10-Year Limited Warranty

10-YEAR REPLACEMENT AVAILABILITY

COLORS AND FINISHES

Available in any color!

NOTE: Colors that are pre-qualified to meet Sustain™ portfolio requirements are available upon request. Other made-to-order colors must be evaluated if sustainability criteria is required. Custom colors are available, for options contact Specials, abpspecials@armstrongceilings.com

360° PAINTED GRID

Suspension System

Declare.

RECYCLED CONTENT
UP TO 30%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK
Human Health
Climate Health
Ecosystem Health
Circular Economy
3rd Party CDPH

VISUAL SELECTION / PERFORMANCE / PACKAGING

	Item No. ◆	Description	Rout Spacing	Dimensions (Inches)	HANGER SPACING* LBS/LF 4 FT.	HANGER SPACING* LBS/LF 5 FT.	Seismic Category	Fire Guard™	CleanAssure™ Disinfectable Panels: Fog	Spray	Wipe	Pieces/ Carton	LF/ Carton
360° Painted Baked Polyester Paint for Exposed Grid Applications Available in White and Black Only													
Prelude® XL® 15/16" (grid end detail not painted)	730136_ _	12' HD Main Beam	24" O.C.	144 × 15/16 × 1-11/16"	16.73	8.73	•	N/A	•	•	•	20	240
	XL734036_ _	4' Cross Tee	24" O.C.	48 × 15/16 × 1-11/16"	12.25	N/A	•	N/A	•	•	•	60	240
	XL732036_ _	2' Cross Tee	N/A	24 × 15/16 × 1-11/16"	61.33 @ 2'	N/A	•	N/A	•	•	•	60	120
Suprafine® XL® 9/16" (grid end detail not painted)	750136_ _	12' HD Main Beam	24" O.C.	144 × 9/16 × 1-11/16"	16.86	8.29	•	N/A	•	•	•	20	240
	XL754036_ _	4' Cross Tee	24" O.C.	48 × 9/16 × 1-11/16"	10.34	N/A	•	N/A	•	•	•	60	240
	XL752036_ _	2' Cross Tee	N/A	24 × 9/16 × 1-11/16"	51.83 @ 2'	N/A	•	N/A	•	•	•	60	120
Molding	780036_ _	12' Hemmed Angle Molding	N/A	144 × 7/8 × 7/8"	N/A	N/A	•	N/A	•	•	•	30	360
	780436_ _	12' Hemmed Angle Molding	N/A	144 × 9/16 × 7/8"	N/A	N/A	•	N/A	•	•	•	30	360
Custom 360° Grid for Exposed Grid Applications													
	Custom 360° Colors Available in custom 360 painted finish, for options contact Specials, abpspecials@armstrongceilings.com												
Custom 360° Powder Coated Grid for Installations with Matching Axiom and Suspension Systems Painted to match Axiom Trim													
Prelude XL 15/16"	AX73013_ _ _	12' HD Main Beam	24" O.C.	144 × 15/16 × 1-11/16"	16.73	8.73	•	N/A	•	•	•	20	240
	AX73403_ _ _	4' Cross Tee	24" O.C.	48 × 15/16 × 1-11/16"	7.8	N/A	•	N/A	•	•	•	60	240
	AX73203_ _ _	2' Cross Tee	N/A	24 × 15/16 × 1-11/16"	36.0 @ 2'	N/A	•	N/A	•	•	•	60	120
Suprafine® XL® 9/16"	AX75013_ _ _	12' HD Main Beam	24" O.C.	144 × 9/16 × 1-11/16"	16.86	10.62	•	N/A	•	•	•	20	240
	AX75403_ _ _	4' Cross Tee	24" O.C.	48 × 9/16 × 1-11/16"	10.34	N/A	•	N/A	•	•	•	60	240
	AX75203_ _ _	2' Cross Tee	N/A	24 × 9/16 × 1-11/16"	51.83 @ 2'	N/A	•	N/A	•	•	•	60	120
Molding	AX78003_ _	12' Hemmed Angle Molding	N/A	144 × 7/8 × 7/8"	N/A	N/A	•	N/A	•	•	•	30	360

◆ When specifying or ordering items with a color or finish, add the two-or three-letter suffix to the end of the item number (e.g. 79013 L G _ – Light Grey)
* Simple Span
** Powder-coated paint only

Dots represent high level of performance.

ASTM Class
HD – Heavy-duty
ID – Intermediate-duty
LD – Light-duty

DETAILS

Baked Polyester, Custom 360 Powder Coated

Custom 360 Painted Colors



PHYSICAL DATA

Material
Hot dipped galvanized steel

Surface Finish
2.0 mil powder-coated painted surface or baked polyester paint

Manufactured and tested in accordance with ASTM C635

Cross Tee/Main Beam Interface
Override

End Detail
Main Beam: Staked-on clip
XL® Cross Tee: Staked-on clip

Seismic Restraint
NOTE: For floating installations refer to ASCE 7-10 for seismic requirements.

Main Beams	Minimum LBS. to pull out compression/tension
730136/750136	330.0
Cross Tees	**Minimum LBS. to pull out compression/tension**

All XL cross tees exceed 300 lbs. in compression/tension

Installation Consideration
If pop riveting must be used on powder-coated material, pre-drill with a sharp 1/8" drill bit to minimize potential paint chipping.

If additional routs are needed for installation, please use the Field Rout Tool (item 7876) or the GC3W clip.

Design Considerations
All acoustical grid and Axiom trim accessories (a.k.a. clips) are supplied as unpainted items for baked polyester and powder-coated grid. Exposed clips will need to be field painted after installation, if required for the project. This ensures accessories meet the tested performance criteria and adhere to AWI installation instructions and warrantied products or systems.

ICC Reports
For areas under ICC jurisdiction, see ICC evaluation report number ESR-1308 for allowable values and/or conditions of use concerning the suspension system components listed on this page. The report is subject to reexamination, revisions, and possible cancellation.

Warranty
See warranty details in the back of this catalog

TechLine / 877 276-7876
armstrongceilings.com/360paint
BPCS-3634-1125

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and Well Building Standard™ are trademarks of the International WELL Building Institute; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong® World Industries