

Dusk Wall Panel Matte

Style Number	CT70K
Composition	Porcelain
Tile Type	Wall Panel
Body Type	Colorbody Glazed Porcelain
Finish	Matte
Nominal Dimensions	12" x 24" 30.48 cm x 60.96 cm
Actual Dimensions	11.69" x 23.46" 29.7 cm x 59.6 cm
Overall Thickness	0.354" 9 mm
Edge Profile	Rectified
Country Of Origin	United States
Installation Area	Walls
Retail Unit Of Measure	Sold by the box quantity
Number of Faces	Approx. 100

Packaging

Pieces per Carton	7
Area per Carton	13.56 ft²
Weight per Carton	53.44 lbs
Area per Pallet	542.4 ft²
Boxes per Pallet	40 boxes

Recommended Installation Method

Grout Joint Requirement: Minimum of 1/8"

Offset Requirements: For a running bond / brick / staggered installation methods. Tiles with a side larger than 15": 33% offset or less. Tiles with a side smaller than 15": 50% offset or less.

Performance + Testing

Shade Variation	V2
Breaking Strength (ASTM C648)	≥ 250 lbf
Water Absorption (ASTM C373) %	≤ 0.50% (Impervious (Porcelain))
Scratch Hardness (ASTM MOHS)	7
Frost Resistance (ASTM C1026)	Resistant
Chemical Resistance (ASTM C650)	Class A
Stain Resistance (ASTM C1378)	Class A
Wear Rating	*0 (Walls Only)

*Not suitable for floors. Use only on walls or vertical surfaces.

Areas of Application

Interior Walls/Backsplash	✓	Interior Wet Plus
Interior Dry Floors		Exterior Wet Floors
Interior Wet Floors		Exterior Walls
Shower Floors		Oils / Grease



Warranties

[1 Year Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

[Ceramic Porcelain Step By Step Installation](#)

[Maintenance Guidelines](#)