

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

USG Mars™ Acoustical Panels with
ClimaPlus™ Performance,
and USG Donn® Brand DX®
Acoustical Suspension System

Photo this page:
Chinook Regional Hospital
Architect: Perkins + Will / KRA / Group2 / Stuart Olson
Photo: ©Andrew Latreille

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050



Limited color options available.
See Ceiling Solutions Color
Program for details.

FEATURES AND BENEFITS

- Balanced acoustics. High-NRC and High-CAC.
- Compatible with USG Logix™ Integrated System.
- Monolithic, structured ceiling visual using standard components.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish—impact and scratch resistant.
- Coordinates visually with USG Halcyon™ Logix™ Acoustical Panels for open/closed-plan applications.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- USG Mars™/Mars™ High-NRC Logix™ Acoustical Panels are part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.

APPLICATIONS

- Open-plan Offices
- Conference Rooms
- Reception and Lobby Areas
- Media Centers and Libraries
- Airports
- Spaces with Indirect or Natural Lighting

SUBSTRATE

- Wet-formed Mineral Fiber

Fine-Textured Panel

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ LOGIX™ FIELD PANELS 75/35

USG MARS™ LOGIX™ CHANNEL PANELS 75/35

Edge	Panel Size ⁵	Fire Class	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC ¹⁰	CAC Min.							
				NRC	CAC						HRC	
SQ	20"x24"x3/4"	Class A	80182	0.75	35	0.90	White	A, B	Low		73%	\$\$
	20"x54"x3/4"	Class A	86519	0.75	35	0.90	White	A	Low		73%	\$\$
	20"x56"x3/4"	Class A	86520	0.75	35	0.90	White	A	Low		73%	\$\$
	20"x60"x3/4"	Class A	86160	0.75	35	0.90	White	A	Low		73%	\$\$
	21"x24"x3/4"	Class A	86522	0.75	35	0.90	White	A, B	Low		73%	\$\$
	21"x48"x3/4"	Class A	86523	0.75	35	0.90	White	A	Low		73%	\$\$
	22"x24"x3/4"	Class A	86524	0.75	35	0.90	White	A, B	Low		73%	\$\$
	22"x48"x3/4"	Class A	86525	0.75	35	0.90	White	A	Low		73%	\$\$
	24"x24"x3/4"	Class A	86185	0.75	35	0.90	White	A, B	Low		73%	\$\$
	24"x42"x3/4"	Class A	86527	0.75	35	0.90	White	A	Low		73%	\$\$
	24"x44"x3/4"	Class A	86528	0.75	35	0.90	White	A	Low		73%	\$\$
	24"x48"x3/4"	Class A	88185	0.75	35	0.90	White	A	Low		73%	\$\$
	24"x72"x3/4"	Class A	86223	0.75	35	0.90	White	A	Low		73%	\$\$
	27"x30"x3/4"	Class A	86530	0.75	35	0.90	White	A	Low		73%	\$\$
	27"x60"x3/4"	Class A	86531	0.75	35	0.90	White	A	Low		73%	\$\$
	28"x30"x3/4"	Class A	86532	0.75	35	0.90	White	A	Low		73%	\$\$
	28"x60"x3/4"	Class A	86533	0.75	35	0.90	White	A	Low		73%	\$\$
	30"x30"x3/4"	Class A	86815	0.75	35	0.90	White	A	Low		73%	\$\$
	30"x54"x3/4"	Class A	86503	0.75	35	0.90	White	A	Low		73%	\$\$
	30"x56"x3/4"	Class A	86535	0.75	35	0.90	White	A	Low		73%	\$\$
	30"x60"x3/4"	Class A	86536	0.75	35	0.90	White	A	Low		73%	\$\$
SQ	4"x48"x3/4"	Class A	86514	0.75	35	0.90	White	A	Low		73%	\$\$
	4"x60"x3/4"	Class A	86515	0.75	35	0.90	White	A	Low		73%	\$\$
	4"x72"x3/4"	Class A	86537	0.75	35	0.90	White	A	Low		73%	\$\$
	6"x48"x3/4"	Class A	86325	0.75	35	0.90	White	A	Low		73%	\$\$
	6"x60"x3/4"	Class A	86507	0.75	35	0.90	White	A	Low		73%	\$\$
	6"x72"x3/4"	Class A	86538	0.75	35	0.90	White	A	Low		73%	\$\$
	12"x12"x3/4"	Class A	86134	0.75 ⁸	35 ⁹	0.90	White	A, B	Low		73%	\$\$
	12"x24"x3/4"	Class A	86289	0.75	35	0.90	White	A, B	Low		73%	\$\$
	12"x48"x3/4"	Class A	86516	0.75	35	0.90	White	A	Low		73%	\$\$
	12"x60"x3/4"	Class A	86517	0.75	35	0.90	White	A	Low		73%	\$\$
	12"x72"x3/4"	Class A	86518	0.75	35	0.90	White	A	Low		73%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ LOGIX™ FIELD PANELS 75/35

USG MARS™ LOGIX™ CHANNEL PANELS 75/35

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x24"x3/4"	Class A	86788	0.75	35	0.90	White	C	Low		73%	\$\$
	20"x54"x3/4"	Class A	86547	0.75	35	0.90	White	C	Low		73%	\$\$
	20"x56"x3/4"	Class A	86548	0.75	35	0.90	White	C	Low		73%	\$\$
	20"x60"x3/4"	Class A	86905	0.75	35	0.90	White	C	Low		73%	\$\$
	21"x24"x3/4"	Class A	86550	0.75	35	0.90	White	C	Low		73%	\$\$
	21"x48"x3/4"	Class A	86551	0.75	35	0.90	White	C	Low		73%	\$\$
	22"x24"x3/4"	Class A	86552	0.75	35	0.90	White	C	Low		73%	\$\$
	22"x48"x3/4"	Class A	86553	0.75	35	0.90	White	C	Low		73%	\$\$
	24"x24"x3/4"	Class A	86785	0.75	35	0.90	White	C	Low		73%	\$\$
	24"x42"x3/4"	Class A	86555	0.75	35	0.90	White	C	Low		73%	\$\$
	24"x44"x3/4"	Class A	86556	0.75	35	0.90	White	C	Low		73%	\$\$
	24"x48"x3/4"	Class A	88785	0.75	35	0.90	White	C	Low		73%	\$\$
	24"x72"x3/4"	Class A	86166	0.75	35	0.90	White	C	Low		73%	\$\$
	27"x30"x3/4"	Class A	86557	0.75	35	0.90	White	C	Low		73%	\$\$
	27"x60"x3/4"	Class A	86558	0.75	35	0.90	White	C	Low		73%	\$\$
	28"x30"x3/4"	Class A	86559	0.75	35	0.90	White	C	Low		73%	\$\$
	28"x60"x3/4"	Class A	86560	0.75	35	0.90	White	C	Low		73%	\$\$
	30"x30"x3/4"	Class A	86875	0.75	35	0.90	White	C	Low		73%	\$\$
	30"x54"x3/4"	Class A	88686	0.75	35	0.90	White	C	Low		73%	\$\$
	30"x56"x3/4"	Class A	86563	0.75	35	0.90	White	C	Low		73%	\$\$
	30"x60"x3/4"	Class A	86564	0.75	35	0.90	White	C	Low		73%	\$\$
SLT	4"x48"x3/4"	Class A	86540	0.75	35	0.90	White	C	Low		73%	\$\$
	4"x60"x3/4"	Class A	86541	0.75	35	0.90	White	C	Low		73%	\$\$
	4"x72"x3/4"	Class A	86565	0.75	35	0.90	White	C	Low		73%	\$\$
	6"x48"x3/4"	Class A	86542	0.75	35	0.90	White	C	Low		73%	\$\$
	6"x60"x3/4"	Class A	86543	0.75	35	0.90	White	C	Low		73%	\$\$
	6"x72"x3/4"	Class A	86566	0.75	35	0.90	White	C	Low		73%	\$\$
	12"x12"x3/4"	Class A	86135	0.75 ⁸	35 ⁹	0.90	White	C	Low		73%	\$\$
	12"x24"x3/4"	Class A	86245	0.75 ⁸	35 ⁹	0.90	White	C	Low		73%	\$\$
	12"x48"x3/4"	Class A	86544	0.75	35	0.90	White	C	Low		73%	\$\$
	12"x60"x3/4"	Class A	86545	0.75	35	0.90	White	C	Low		73%	\$\$
	12"x72"x3/4"	Class A	86546	0.75	35	0.90	White	C	Low		73%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ LOGIX™ FIELD PANELS 75/35

USG MARS™ LOGIX™ CHANNEL PANELS 75/35

Edge	Panel Size ⁵	Fire Class	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC ¹⁰	CAC Min.							
FLB	20"x24"x3/4"	Class A	86329	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	20"x54"x3/4"	Class A	88845	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	20"x56"x3/4"	Class A	86571	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	20"x60"x3/4"	Class A	86164	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	21"x24"x3/4"	Class A	88840	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	21"x48"x3/4"	Class A	86573	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	22"x24"x3/4"	Class A	86574	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	22"x48"x3/4"	Class A	86575	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	24"x24"x3/4"	Class A	86985	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	24"x42"x3/4"	Class A	86577	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	24"x44"x3/4"	Class A	86578	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	24"x48"x3/4"	Class A	88985	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	24"x72"x3/4"	Class A	88996	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	27"x30"x3/4"	Class A	86850	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	27"x60"x3/4"	Class A	86579	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	28"x30"x3/4"	Class A	86834	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	28"x60"x3/4"	Class A	86580	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	30"x30"x3/4"	Class A	86830	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	30"x54"x3/4"	Class A	86831	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	30"x56"x3/4"	Class A	86583	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	30"x60"x3/4"	Class A	86267	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
FLB	4"x48"x3/4"	Class A	86568	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	4"x60"x3/4"	Class A	86569	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	4"x72"x3/4"	Class A	86584	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	6"x48"x3/4"	Class A	88887	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	6"x60"x3/4"	Class A	86835	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	6"x72"x3/4"	Class A	86567	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	12"x12"x3/4"	Class A	86136	0.75 ⁸	35 ⁹	0.90	White	D,E,F,G	Low		73%	\$\$
	12"x24"x3/4"	Class A	86242	0.75 ⁸	35 ⁹	0.90	White	D,E,F,G	Low		73%	\$\$
	12"x48"x3/4"	Class A	86321	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	12"x60"x3/4"	Class A	88885	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$
	12"x72"x3/4"	Class A	86570	0.75	35	0.90	White	D,E,F,G	Low		73%	\$\$

Low Emissions (VOC)
Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 80/35

Plant-Based Binder⁷

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	20"x24"x7/8"	Class A	80184	0.80	35	0.90	White	A, B	Low		74%	\$\$
	20"x54"x7/8"	Class A	86410	0.80	35	0.90	White	A	Low		74%	\$\$
	20"x56"x7/8"	Class A	86411	0.80	35	0.90	White	A	Low		74%	\$\$
	20"x60"x7/8"	Class A	89501	0.80	35	0.90	White	A	Low		74%	\$\$
	21"x24"x7/8"	Class A	86414	0.80	35	0.90	White	A, B	Low		74%	\$\$
	21"x48"x7/8"	Class A	86415	0.80	35	0.90	White	A	Low		74%	\$\$
	22"x24"x7/8"	Class A	86416	0.80	35	0.90	White	A, B	Low		74%	\$\$
	22"x48"x7/8"	Class A	86417	0.80	35	0.90	White	A	Low		74%	\$\$
	24"x24"x7/8"	Class A	86100	0.80	35	0.90	White	A, B	Low		74%	\$\$
	24"x42"x7/8"	Class A	86419	0.80	35	0.90	White	A	Low		74%	\$\$
	24"x44"x7/8"	Class A	86420	0.80	35	0.90	White	A	Low		74%	\$\$
	24"x48"x7/8"	Class A	86300	0.80	35	0.90	White	A	Low		74%	\$\$
	24"x72"x7/8"	Class A	86360	0.80	35	0.90	White	A	Low		74%	\$\$
	27"x30"x7/8"	Class A	86421	0.80	35	0.90	White	A	Low		74%	\$\$
	27"x60"x7/8"	Class A	86422	0.80	35	0.90	White	A	Low		74%	\$\$
	28"x30"x7/8"	Class A	86423	0.80	35	0.90	White	A	Low		74%	\$\$
	28"x60"x7/8"	Class A	86424	0.80	35	0.90	White	A	Low		74%	\$\$
	30"x30"x7/8"	Class A	86426	0.80	35	0.90	White	A	Low		74%	\$\$
	30"x54"x7/8"	Class A	86427	0.80	35	0.90	White	A	Low		74%	\$\$
	30"x56"x7/8"	Class A	86428	0.80	35	0.90	White	A	Low		74%	\$\$
	30"x60"x7/8"	Class A	86429	0.80	35	0.90	White	A	Low		74%	\$\$
SQ 	4"x48"x7/8"	Class A	86402	0.80	35	0.90	White	A	Low		74%	\$\$
	4"x60"x7/8"	Class A	86403	0.80	35	0.90	White	A	Low		74%	\$\$
	4"x72"x7/8"	Class A	86405	0.80	35	0.90	White	A	Low		74%	\$\$
	6"x48"x7/8"	Class A	86404	0.80	35	0.90	White	A	Low		74%	\$\$
	6"x60"x7/8"	Class A	86145	0.80	35	0.90	White	A	Low		74%	\$\$
	6"x72"x7/8"	Class A	86406	0.80	35	0.90	White	A	Low		74%	\$\$
	12"x48"x7/8"	Class A	86407	0.80	35	0.90	White	A	Low		74%	\$\$
	12"x60"x7/8"	Class A	86408	0.80	35	0.90	White	A	Low		74%	\$\$
	12"x72"x7/8"	Class A	86409	0.80	35	0.90	White	A	Low		74%	\$\$

Low Emissions (VOC)
Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 80/35

Plant-Based Binder⁷

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 80/35

Plant-Based Binder⁷

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x24"x7/8"	Class A	80183	0.80	35	0.90	White	C	Low		74%	\$\$
	20"x54"x7/8"	Class A	86447	0.80	35	0.90	White	C	Low		74%	\$\$
	20"x56"x7/8"	Class A	86448	0.80	35	0.90	White	C	Low		74%	\$\$
	20"x60"x7/8"	Class A	86449	0.80	35	0.90	White	C	Low		74%	\$\$
	21"x24"x7/8"	Class A	86451	0.80	35	0.90	White	C	Low		74%	\$\$
	21"x48"x7/8"	Class A	86452	0.80	35	0.90	White	C	Low		74%	\$\$
	22"x24"x7/8"	Class A	86453	0.80	35	0.90	White	C	Low		74%	\$\$
	22"x48"x7/8"	Class A	86454	0.80	35	0.90	White	C	Low		74%	\$\$
	24"x24"x7/8"	Class A	87200	0.80	35	0.90	White	C	Low		74%	\$\$
	24"x42"x7/8"	Class A	86456	0.80	35	0.90	White	C	Low		74%	\$\$
	24"x44"x7/8"	Class A	86457	0.80	35	0.90	White	C	Low		74%	\$\$
	24"x48"x7/8"	Class A	89600	0.80	35	0.90	White	C	Low		74%	\$\$
	24"x72"x7/8"	Class A	89660	0.80	35	0.90	White	C	Low		74%	\$\$
	27"x30"x7/8"	Class A	86458	0.80	35	0.90	White	C	Low		74%	\$\$
	27"x60"x7/8"	Class A	86460	0.80	35	0.90	White	C	Low		74%	\$\$
	28"x30"x7/8"	Class A	86459	0.80	35	0.90	White	C	Low		74%	\$\$
	28"x60"x7/8"	Class A	86461	0.80	35	0.90	White	C	Low		74%	\$\$
	30"x30"x7/8"	Class A	86500	0.80	35	0.90	White	C	Low		74%	\$\$
	30"x54"x7/8"	Class A	86464	0.80	35	0.90	White	C	Low		74%	\$\$
	30"x56"x7/8"	Class A	86465	0.80	35	0.90	White	C	Low		74%	\$\$
	30"x60"x7/8"	Class A	86466	0.80	35	0.90	White	C	Low		74%	\$\$
SLT	4"x48"x7/8"	Class A	86440	0.80	35	0.90	White	C	Low		74%	\$\$
	4"x60"x7/8"	Class A	86441	0.80	35	0.90	White	C	Low		74%	\$\$
	4"x72"x7/8"	Class A	86467	0.80	35	0.90	White	C	Low		74%	\$\$
	6"x48"x7/8"	Class A	86442	0.80	35	0.90	White	C	Low		74%	\$\$
	6"x60"x7/8"	Class A	86443	0.80	35	0.90	White	C	Low		74%	\$\$
	6"x72"x7/8"	Class A	86468	0.80	35	0.90	White	C	Low		74%	\$\$
	12"x48"x7/8"	Class A	86444	0.80	35	0.90	White	C	Low		74%	\$\$
	12"x60"x7/8"	Class A	86445	0.80	35	0.90	White	C	Low		74%	\$\$
	12"x72"x7/8"	Class A	86446	0.80	35	0.90	White	C	Low		74%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



UL Classified

Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
FLB	20"x24"x7/8"	Class A	86693	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	20"x54"x7/8"	Class A	86479	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	20"x56"x7/8"	Class A	86480	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	20"x60"x7/8"	Class A	86481	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	21"x24"x7/8"	Class A	86483	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	21"x48"x7/8"	Class A	86484	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	22"x24"x7/8"	Class A	86485	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	22"x48"x7/8"	Class A	86486	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	24"x24"x7/8"	Class A	87100	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	24"x42"x7/8"	Class A	86488	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	24"x44"x7/8"	Class A	86489	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	24"x48"x7/8"	Class A	89500	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	24"x72"x7/8"	Class A	89670	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	27"x30"x7/8"	Class A	86490	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	27"x60"x7/8"	Class A	86491	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	28"x30"x7/8"	Class A	86492	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	28"x60"x7/8"	Class A	86493	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	30"x30"x7/8"	Class A	86400	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	30"x54"x7/8"	Class A	86501	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	30"x56"x7/8"	Class A	86496	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	30"x60"x7/8"	Class A	86497	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
FLB	4"x48"x7/8"	Class A	86475	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	4"x60"x7/8"	Class A	86476	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	4"x72"x7/8"	Class A	86473	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	6"x48"x7/8"	Class A	86331	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	6"x60"x7/8"	Class A	86333	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	6"x72"x7/8"	Class A	86474	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	12"x48"x7/8"	Class A	86505	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	12"x60"x7/8"	Class A	86477	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$
	12"x72"x7/8"	Class A	86478	0.80	35	0.90	White	D,E,F,G	Low		74%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 85/35

Plant-Based Binder⁷

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	20"x24"x7/8"	Class A	80186	0.85	35	0.90	White	A, B	Low		72%	\$\$
	20"x54"x7/8"	Class A	80100	0.85	35	0.90	White	A	Low		72%	\$\$
	20"x56"x7/8"	Class A	80101	0.85	35	0.90	White	A	Low		72%	\$\$
	20"x60"x7/8"	Class A	80102	0.85	35	0.90	White	A	Low		72%	\$\$
	21"x24"x7/8"	Class A	80103	0.85	35	0.90	White	A,B	Low		72%	\$\$
	21"x48"x7/8"	Class A	80104	0.85	35	0.90	White	A	Low		72%	\$\$
	22"x24"x7/8"	Class A	80105	0.85	35	0.90	White	A,B	Low		72%	\$\$
	22"x48"x7/8"	Class A	80106	0.85	35	0.90	White	A	Low		72%	\$\$
	24"x24"x7/8"	Class A	88134	0.85	35	0.90	White	A,B	Low		72%	\$\$
	24"x42"x7/8"	Class A	80107	0.85	35	0.90	White	A	Low		72%	\$\$
	24"x44"x7/8"	Class A	80108	0.85	35	0.90	White	A	Low		72%	\$\$
	24"x48"x7/8"	Class A	89134	0.85	35	0.90	White	A	Low		72%	\$\$
	24"x72"x7/8"	Class A	89663	0.85	35	0.90	White	A	Low		72%	\$\$
	27"x30"x7/8"	Class A	80109	0.85	35	0.90	White	A	Low		72%	\$\$
	27"x60"x7/8"	Class A	80110	0.85	35	0.90	White	A	Low		72%	\$\$
	28"x30"x7/8"	Class A	80111	0.85	35	0.90	White	A	Low		72%	\$\$
	28"x60"x7/8"	Class A	80112	0.85	35	0.90	White	A	Low		72%	\$\$
	30"x30"x7/8"	Class A	80113	0.85	35	0.90	White	A	Low		72%	\$\$
	30"x54"x7/8"	Class A	80114	0.85	35	0.90	White	A	Low		72%	\$\$
	30"x56"x7/8"	Class A	80115	0.85	35	0.90	White	A	Low		72%	\$\$
	30"x60"x7/8"	Class A	89140	0.85	35	0.90	White	A	Low		72%	\$\$
SQ 	4"x48"x7/8"	Class A	80116	0.85	35	0.90	White	A	Low		72%	\$\$
	4"x60"x7/8"	Class A	80117	0.85	35	0.90	White	A	Low		72%	\$\$
	4"x72"x7/8"	Class A	80118	0.85	35	0.90	White	A	Low		72%	\$\$
	6"x48"x7/8"	Class A	80119	0.85	35	0.90	White	A	Low		72%	\$\$
	6"x60"x7/8"	Class A	80120	0.85	35	0.90	White	A	Low		72%	\$\$
	6"x72"x7/8"	Class A	80121	0.85	35	0.90	White	A	Low		72%	\$\$
	12"x12"x7/8"	Class A	80122	0.85	35	0.90	White	A, B	Low		72%	\$\$
	12"x24"x7/8"	Class A	86665	0.85	35	0.90	White	A, B	Low		72%	\$\$
	12"x48"x7/8"	Class A	80123	0.85	35	0.90	White	A	Low		72%	\$\$
	12"x60"x7/8"	Class A	80124	0.85	35	0.90	White	A	Low		72%	\$\$
	12"x72"x7/8"	Class A	80125	0.85	35	0.90	White	A	Low		72%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
ULCOM/GG
UL 2818



UL Classified

Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x24"x7/8"	Class A	80185	0.85	35	0.90	White	C	Low		72%	\$
	20"x54"x7/8"	Class A	80126	0.85	35	0.90	White	C	Low		72%	\$
	20"x56"x7/8"	Class A	80127	0.85	35	0.90	White	C	Low		72%	\$
	20"x60"x7/8"	Class A	80128	0.85	35	0.90	White	C	Low		72%	\$
	21"x24"x7/8"	Class A	80129	0.85	35	0.90	White	C	Low		72%	\$
	21"x48"x7/8"	Class A	80130	0.85	35	0.90	White	C	Low		72%	\$
	22"x24"x7/8"	Class A	80131	0.85	35	0.90	White	C	Low		72%	\$
	22"x48"x7/8"	Class A	80132	0.85	35	0.90	White	C	Low		72%	\$
	24"x24"x7/8"	Class A	88135	0.85	35	0.90	White	C	Low		72%	\$
	24"x42"x7/8"	Class A	80133	0.85	35	0.90	White	C	Low		72%	\$
	24"x44"x7/8"	Class A	80134	0.85	35	0.90	White	C	Low		72%	\$
	24"x48"x7/8"	Class A	89135	0.85	35	0.90	White	C	Low		72%	\$
	24"x72"x7/8"	Class A	89665	0.85	35	0.90	White	C	Low		72%	\$
	27"x30"x7/8"	Class A	80135	0.85	35	0.90	White	C	Low		72%	\$
	27"x60"x7/8"	Class A	80136	0.85	35	0.90	White	C	Low		72%	\$
	28"x30"x7/8"	Class A	80137	0.85	35	0.90	White	C	Low		72%	\$
	28"x60"x7/8"	Class A	80138	0.85	35	0.90	White	C	Low		72%	\$
	30"x30"x7/8"	Class A	80139	0.85	35	0.90	White	C	Low		72%	\$
	30"x54"x7/8"	Class A	80140	0.85	35	0.90	White	C	Low		72%	\$
	30"x56"x7/8"	Class A	80141	0.85	35	0.90	White	C	Low		72%	\$
	30"x60"x7/8"	Class A	89141	0.85	35	0.90	White	C	Low		72%	\$
SLT	4"x48"x7/8"	Class A	80142	0.85	35	0.90	White	C	Low		72%	\$
	4"x60"x7/8"	Class A	80143	0.85	35	0.90	White	C	Low		72%	\$
	4"x72"x7/8"	Class A	80144	0.85	35	0.90	White	C	Low		72%	\$
	6"x48"x7/8"	Class A	80145	0.85	35	0.90	White	C	Low		72%	\$
	6"x60"x7/8"	Class A	80146	0.85	35	0.90	White	C	Low		72%	\$
	6"x72"x7/8"	Class A	80147	0.85	35	0.90	White	C	Low		72%	\$
	12"x12"x7/8"	Class A	80148	0.85	35	0.90	White	C	Low		72%	\$
	12"x24"x7/8"	Class A	86664	0.85	35	0.90	White	C	Low		72%	\$
	12"x48"x7/8"	Class A	80149	0.85	35	0.90	White	C	Low		72%	\$
	12"x60"x7/8"	Class A	80150	0.85	35	0.90	White	C	Low		72%	\$
	12"x72"x7/8"	Class A	80151	0.85	35	0.90	White	C	Low		72%	\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 85/35

Plant-Based Binder⁷

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 85/35

Plant-Based Binder⁷

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 85/35

Plant-Based Binder⁷

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 85/35

Plant-Based Binder⁷

Edge	Panel Size ⁵	Fire Class	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC ¹⁰	CAC Min.							
				NRC	CAC						HRC	
FLB	20"x24"x7/8"	Class A	86499	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	20"x54"x7/8"	Class A	80152	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	20"x56"x7/8"	Class A	80153	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	20"x60"x7/8"	Class A	80154	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	21"x24"x7/8"	Class A	80155	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	21"x48"x7/8"	Class A	80156	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	22"x24"x7/8"	Class A	80157	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	22"x48"x7/8"	Class A	80158	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	24"x24"x7/8"	Class A	88136	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	24"x42"x7/8"	Class A	80159	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	24"x44"x7/8"	Class A	80160	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	24"x48"x7/8"	Class A	89136	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	24"x72"x7/8"	Class A	89668	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	27"x30"x7/8"	Class A	80161	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	27"x60"x7/8"	Class A	80162	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	28"x30"x7/8"	Class A	80163	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	28"x60"x7/8"	Class A	80164	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	30"x30"x7/8"	Class A	80165	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	30"x54"x7/8"	Class A	80166	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	30"x56"x7/8"	Class A	80167	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	30"x60"x7/8"	Class A	89142	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
FLB	4"x48"x7/8"	Class A	80168	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	4"x60"x7/8"	Class A	80169	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	4"x72"x7/8"	Class A	80170	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	6"x48"x7/8"	Class A	80171	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	6"x60"x7/8"	Class A	80172	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	6"x72"x7/8"	Class A	80173	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	12"x12"x7/8"	Class A	80174	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	12"x24"x7/8"	Class A	86663	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	12"x48"x7/8"	Class A	80175	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	12"x60"x7/8"	Class A	80176	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$
	12"x72"x7/8"	Class A	80177	0.85	35	0.90	White	D,E,F,G	Low		72%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
ULCOM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 90/30

Plant-Based Binder⁷

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	20"x24"x1"	Class A	80188	0.90	30	0.90	White	A, B	Low		71%	\$\$
	20"x54"x1"	Class A	80200	0.90	30	0.90	White	A	Low		71%	\$\$
	20"x56"x1"	Class A	80201	0.90	30	0.90	White	A	Low		71%	\$\$
	20"x60"x1"	Class A	80202	0.90	30	0.90	White	A	Low		71%	\$\$
	21"x24"x1"	Class A	80203	0.90	30	0.90	White	A,B	Low		71%	\$\$
	21"x48"x1"	Class A	80204	0.90	30	0.90	White	A	Low		71%	\$\$
	22"x24"x1"	Class A	80205	0.90	30	0.90	White	A,B	Low		71%	\$\$
	22"x48"x1"	Class A	80206	0.90	30	0.90	White	A	Low		71%	\$\$
	24"x24"x1"	Class A	88137	0.90	30	0.90	White	A,B	Low		71%	\$\$
	24"x42"x1"	Class A	80207	0.90	30	0.90	White	A	Low		71%	\$\$
	24"x44"x1"	Class A	80208	0.90	30	0.90	White	A	Low		71%	\$\$
	24"x48"x1"	Class A	89137	0.90	30	0.90	White	A	Low		71%	\$\$
	24"x72"x1"	Class A	89674	0.90	30	0.90	White	A	Low		71%	\$\$
	27"x30"x1"	Class A	80209	0.90	30	0.90	White	A	Low		71%	\$\$
	27"x60"x1"	Class A	80210	0.90	30	0.90	White	A	Low		71%	\$\$
	28"x30"x1"	Class A	80211	0.90	30	0.90	White	A	Low		71%	\$\$
	28"x60"x1"	Class A	80212	0.90	30	0.90	White	A	Low		71%	\$\$
	30"x30"x1"	Class A	80213	0.90	30	0.90	White	A	Low		71%	\$\$
	30"x54"x1"	Class A	80214	0.90	30	0.90	White	A	Low		71%	\$\$
	30"x56"x1"	Class A	80215	0.90	30	0.90	White	A	Low		71%	\$\$
	30"x60"x1"	Class A	89143	0.90	30	0.90	White	A	Low		71%	\$\$
SQ 	4"x48"x1"	Class A	80216	0.90	30	0.90	White	A	Low		71%	\$\$
	4"x60"x1"	Class A	80217	0.90	30	0.90	White	A	Low		71%	\$\$
	4"x72"x1"	Class A	80218	0.90	30	0.90	White	A	Low		71%	\$\$
	6"x48"x1"	Class A	80219	0.90	30	0.90	White	A	Low		71%	\$\$
	6"x60"x1"	Class A	80220	0.90	30	0.90	White	A	Low		71%	\$\$
	6"x72"x1"	Class A	80221	0.90	30	0.90	White	A	Low		71%	\$\$
	12"x12"x1"	Class A	80222	0.90	30	0.90	White	A, B	Low		71%	\$\$
	12"x24"x1"	Class A	86137	0.90	30	0.90	White	A, B	Low		71%	\$\$
	12"x48"x1"	Class A	80223	0.90	30	0.90	White	A	Low		71%	\$\$
	12"x60"x1"	Class A	80224	0.90	30	0.90	White	A	Low		71%	\$\$
	12"x72"x1"	Class A	80225	0.90	30	0.90	White	A	Low		71%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
ULCOM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 90/30

Plant-Based Binder⁷

Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x24"x1"	Class A	80187	0.90	30	0.90	White	C	Low		71%	\$\$
	20"x54"x1"	Class A	80226	0.90	30	0.90	White	C	Low		71%	\$\$
	20"x56"x1"	Class A	80227	0.90	30	0.90	White	C	Low		71%	\$\$
	20"x60"x1"	Class A	80228	0.90	30	0.90	White	C	Low		71%	\$\$
	21"x24"x1"	Class A	80229	0.90	30	0.90	White	C	Low		71%	\$\$
	21"x48"x1"	Class A	80230	0.90	30	0.90	White	C	Low		71%	\$\$
	22"x24"x1"	Class A	80231	0.90	30	0.90	White	C	Low		71%	\$\$
	22"x48"x1"	Class A	80232	0.90	30	0.90	White	C	Low		71%	\$\$
	24"x24"x1"	Class A	88138	0.90	30	0.90	White	C	Low		71%	\$\$
	24"x42"x1"	Class A	80233	0.90	30	0.90	White	C	Low		71%	\$\$
	24"x44"x1"	Class A	80234	0.90	30	0.90	White	C	Low		71%	\$\$
	24"x48"x1"	Class A	89138	0.90	30	0.90	White	C	Low		71%	\$\$
	24"x72"x1"	Class A	89676	0.90	30	0.90	White	C	Low		71%	\$\$
	27"x30"x1"	Class A	80235	0.90	30	0.90	White	C	Low		71%	\$\$
	27"x60"x1"	Class A	80236	0.90	30	0.90	White	C	Low		71%	\$\$
	28"x30"x1"	Class A	80237	0.90	30	0.90	White	C	Low		71%	\$\$
	28"x60"x1"	Class A	80238	0.90	30	0.90	White	C	Low		71%	\$\$
	30"x30"x1"	Class A	80239	0.90	30	0.90	White	C	Low		71%	\$\$
	30"x54"x1"	Class A	80240	0.90	30	0.90	White	C	Low		71%	\$\$
	30"x56"x1"	Class A	80241	0.90	30	0.90	White	C	Low		71%	\$\$
	30"x60"x1"	Class A	89144	0.90	30	0.90	White	C	Low		71%	\$\$
SLT	4"x48"x1"	Class A	80242	0.90	30	0.90	White	C	Low		71%	\$\$
	4"x60"x1"	Class A	80243	0.90	30	0.90	White	C	Low		71%	\$\$
	4"x72"x1"	Class A	80244	0.90	30	0.90	White	C	Low		71%	\$\$
	6"x48"x1"	Class A	80245	0.90	30	0.90	White	C	Low		71%	\$\$
	6"x60"x1"	Class A	80246	0.90	30	0.90	White	C	Low		71%	\$\$
	6"x72"x1"	Class A	80247	0.90	30	0.90	White	C	Low		71%	\$\$
	12"x12"x1"	Class A	80248	0.90	30	0.90	White	C	Low		71%	\$\$
	12"x24"x1"	Class A	86138	0.90	30	0.90	White	C	Low		71%	\$\$
	12"x48"x1"	Class A	80249	0.90	30	0.90	White	C	Low		71%	\$\$
	12"x60"x1"	Class A	80250	0.90	30	0.90	White	C	Low		71%	\$\$
	12"x72"x1"	Class A	80251	0.90	30	0.90	White	C	Low		71%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 90/30

Plant-Based Binder⁷

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 90/30

Plant-Based Binder⁷

UL Classified												
Edge	Panel Size ⁵	Fire Class	Item No.	NRC ¹⁰	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
FLB	20"x24"x1"	Class A	80181	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	20"x54"x1"	Class A	80252	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	20"x56"x1"	Class A	80253	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	20"x60"x1"	Class A	80254	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	21"x24"x1"	Class A	80255	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	21"x48"x1"	Class A	80256	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	22"x24"x1"	Class A	80257	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	22"x48"x1"	Class A	80258	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	24"x24"x1"	Class A	88139	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	24"x42"x1"	Class A	80259	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	24"x44"x1"	Class A	80260	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	24"x48"x1"	Class A	89139	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	24"x72"x1"	Class A	89678	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	27"x30"x1"	Class A	80261	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	27"x60"x1"	Class A	80262	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	28"x30"x1"	Class A	80263	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	28"x60"x1"	Class A	80264	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	30"x30"x1"	Class A	80265	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	30"x54"x1"	Class A	80266	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	30"x56"x1"	Class A	80267	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	30"x60"x1"	Class A	89145	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
FLB	4"x48"x1"	Class A	80268	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	4"x60"x1"	Class A	80269	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	4"x72"x1"	Class A	80270	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	6"x48"x1"	Class A	80271	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	6"x60"x1"	Class A	80272	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	6"x72"x1"	Class A	80273	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	12"x12"x1"	Class A	80274	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	12"x24"x1"	Class A	86139	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	12"x48"x1"	Class A	80275	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	12"x60"x1"	Class A	80276	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$
	12"x72"x1"	Class A	80277	0.90	30	0.90	White	D,E,F,G	Low		71%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™
ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818

GRID PROFILE OPTIONS

PHYSICAL DATA

30

YEAR LIMITED SYSTEM WARRANTY

• No Visible Sag

• Mold/Mildew Protection

BA

BALANCED ACOUSTICS

HRC

HIGH RECYCLED CONTENT

PB

Plant-Based Binder



A USG DX®	B ⁴ USG Centricitee™ DXT™	C USG DX®	D USG Centricitee™ DXT™	E USG Fineline® DXF™	F USG Fineline® 1/8 DXFF™	G USG Identitee® DXI™

Product literature
System guide: IS268

ASTM E1264 classification
ASTM E1264-22: Type IV, Form 1 and 2, Pattern E & G
ASTM E1264-23: Type A, Form A2.1 and A2.2, Pattern E & G

ASTM E84 and CAN/ULC S102 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
1.01 lb./sq. ft. (3/4")
1.09-1.12 lb./sq. ft (7/8")
1.25 lb./sq. ft (1")

Online tools
usgdesignstudio.com, cgcdesignstudio.com
or usg.ecomedes.com

Thermal resistance
R-2.2 (3/4")

Maintenance
Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean white cloth with water or a mild detergent and wipe surface.

Maximum backloading
See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Notes

- For details see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- Panel face and back surfaces treated with a proprietary broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).
- Maximum 2'x2' with SQ edge panels.
- Stabilizer bar required if opening ≥ 60".
- Additional panel sizes and colors are available. Please contact your local sales representative for details.
- All USG Mars™ High NRC Acoustical Panels with a "plant-based binder" label contain up to 65% plant-based material in the binder. For more information please refer to the USG Mars™ Acoustical Panels Health Product Declaration, available at www.usg.com
- Tested in accordance with ASTM C423; not UL classified for acoustics.
- Tested in accordance with ASTM E1414; not UL classified for acoustics.
- It is not recommended to mix panels with varying NRC values in the same ceiling plane.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

IS274/rev. 7-25
© 2025 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXI, DXT, ECOBLUEPRINT, FINELINE, HALCYON, IDENTITEE, LOGIX, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

