

All Weather/Empire® Base Sheet

Lightly SBS-modified bitumen fiberglass base sheet

PRODUCT INFORMATION

CertainTeed's All Weather/Empire® Base Sheet is a lightly SBS-modified asphaltic base sheet, allowing contractors to dry in a roof quickly and economically when installing All Weather with hot asphalt or cold adhesive. All Weather can also be mechanically attached, and offers better kick-out and lay flat characteristics than our most economical, non-modified base, Glasbase™ Base Sheet.

Product Composition and Features: All Weather/Empire delivers strength and moisture resistance when used as the first ply over nailable, non-nailable, and insulated substrates in BUR or modified asphalt roof systems. This 51 mil base sheet is manufactured with tough, dimensionally stable fiberglass reinforcement that is highly resistant to tearing and punctures. The fiberglass mat is saturated and coated with an SBS-modified asphalt with elastic, waterproofing properties. All Weather/Empire® Base Sheets gets you "in the dry" with a economic, yet robust solution.

APPLICATION METHOD



Fasteners



Hot Asphalt



Cold Adhesive



KEY PRODUCT DETAILS

<i>Roll Dimensions:</i>	39-3/8" X 65' 10"
<i>Nominal Coverage:</i>	Two Squares
<i>Approximate Weight:</i>	70 lbs. per roll
<i>Top Surface:</i>	Fine sand
<i>Back Surface:</i>	Removable release film
<i>Packaging:</i>	Plastic Wraps (25 rolls per pallet)
<i>Compound:</i>	Non-oxidized (flux) asphalt, blended with elastomeric styrene-butadiene-styrene (SBS) polymer and a propitiatory mix of fire resistant chemicals.
<i>Reinforcement:</i>	Support Mat: Heavy duty fiberglass reinforced mat.

CODES AND APPROVALS



State of Florida
Product Approved

TEXAS DEPARTMENT
OF INSURANCE
(RC-47)

ASTM
INTERNATIONAL
Meets or exceeds
ASTM-D4601 Type II
ASTM D6757



STORAGE AND HANDLING

All Weather/Empire® Base Sheet must be stored above ground indoors and protected from the elements. Rolls that are improperly stored or have been on hand for prolonged periods of time may lose their tack. Do not attempt to install rolls that do not exhibit an adequate bond.



For detailed installation instructions and precautions, refer to the CertainTeed Commercial Roof Systems Specifications Manual or contact Commercial Roofing Technical Services.

WARRANTIES

CertainTeed offers Limited (product only) and No Dollar Limit (NDL, product and workmanship) warranties. Warranty type and duration is dependent on roof system configuration and contractor selection. CertainTeed Gold and Silver Star Contractors are eligible to apply for NDL warranties on specific roof projects. For more information, see CertainTeed Commercial Roof Systems Specifications Manual or contact Commercial Roofing Technical Services.

TECHNICAL ASSISTANCE AND SERVICES

CertainTeed provides technical assistance in the design, selection, specification and application guidelines of CertainTeed's Commercial Roof Systems. Architectural and field representatives are available for consultation within each region.

For more information, contact CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM

20 Moores Road, Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](https://www.certainteed.com)

©12/24 CertainTeed, Code No. 01-11-4437-NA-EN