


Patriot™ XL Shingles

PRODUCT INFORMATION

Patriot™ XL shingles reflect the same high manufacturing standards as the rest of CertainTeed's line of roofing products. Patriot XL shingles are built with the industry's toughest fiber glass mat base, and their strict dimensional tolerance assures consistency. Aesthetically pleasing granule color blends produce a classic color selection.



Colors: Please refer to the product brochure or CertainTeed website for the colors available in your region.

Limitations: Use on roofs with slopes greater than 2" per foot. Low-slope applications (2:12 to < 4:12) require an additional waterproofing shingle underlayment. In areas where icing along eaves can cause the back-up of water, apply CertainTeed WinterGuard Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

Product Composition: Patriot XL shingles are composed of a fiber glass mat base. Mineral granules are tightly embedded in carefully refined, water-resistant asphalt. Two pieces of the shingle are firmly laminated together in a special, tough asphaltic cement. All Patriot XL shingles have self-sealing adhesive strips.

Applicable Standards

ASTM D3018 Type I
ASTM D3462
ASTM E108 Class A Fire Resistance
ASTM D3161 Class F Wind Resistance
ASTM D7158 Class H Wind Resistance
UL 790 Class A Fire Resistance
CSA Standard A123.5
Meets TDI Windstorm Requirements

Technical Data:

	Patriot XL
Weight/Square (approx.)	220 to 235 lb *
Dimensions (overall)	42" x 14"
Weather Exposure	6"
Shingles per square	57
Bundles per square	3
Coverage per square	98.7 square feet

*Dependent on manufacturing location. Weight per 100 square feet.

INSTALLATION

Detailed installation instructions are supplied on each bundle of Patriot XL shingles and must be followed. Separate application instructions may also be obtained at www.certainteed.com or by contacting CertainTeed.

Hips and Ridges: For capping hip and ridge apply CertainTeed Shadow Ridge® XL shingles of a like color.

MAINTENANCE

Shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

Patriot XL shingles carry a lifetime or 40-year transferable limited warranty (depending on ownership and building type) against manufacturing defects that cause leaks for the original owner when applied in accordance with CertainTeed's published installation instructions. In addition, Patriot XL shingles carry up to 10-years of SureStart™ Protection. For specific warranty details and limitations, refer to the applicable warranty document (available from the local supplier, roofing contractor or on-line at www.certainteed.com).

TECHNICAL SUPPORT

Technical Service Department: 800-345-1145

e-mail: RPGTS@saint-gobain.com

FOR MORE INFORMATION

Customer Experience Team: 800-233-8990

e-mail: gethelp@saint-gobain.com

Web site: www.certainteed.com