

SUBMITTAL SHEET

High Profile Series™ Wall Battens

Project Name _____

Specification Section _____

Ceiling Type _____

Substrate

Extruded Aluminum

Profile

(Width x Height)

Batten

- | | |
|------------------------------------|----------------------------------|
| ☐ 1" x 3" | ☐ 2" x 2" |
| ☐ 1" x 4" | ☐ 2" x 3" |
| ☐ 1.5" x 3" | ☐ 2" x 4" |
| ☐ 1.5" x 4" | ☐ 2" x 5" |
| | ☐ 2" x 6" |

* Length - minimum 4'-0", maximum S/B 24'-0"

Batten O.C. Spacing

(Center of Batten
to Center of Batten)

- ☐ Project specific: _____

Color/Finish

Beam Finish

- ☐ Cotton White - #0280
☐ Natural - #7163
☐ Decorated Wood-Look
☐ Other # _____

End Caps

- ☐ Yes
☐ No

Grain Direction

(For Decorated
End Caps)

- ☐ Horizontal
☐ Vertical

Splices

- ☐ Yes
☐ No

Exposure

- ☒ Interior

High Profile Series™ Wall Battens

Physical Data

Substrate: Aluminum

Warranty: 1 year Limited Warranty

Seismic Application:

Contact CertainTeed Pre-Con Group for appropriate methods of addressing the specific application on your project.

Flame Spread / Smoke Dev.

Per ASTM E84 – CAN/ULC S102

Flame spread: ≤ 25 / Smoke Dev. ≤ 50
(Class A per ASTM E1264)

Weight: Varies 2.0 – 4.0 lbs./sq.ft.

Wind Load: Per Code

Recycled Content: Minimum of 50%

**Light Reflectance (LR) Coefficient
per ASTM E1264 & ASTM E1477:**

– Cotton White LR = 0.81



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com