

SUBMITTAL SHEET

Tavola™ Round

Project Name _____

Specification Section _____

Ceiling Type _____

Substrate: Aluminum

☐ .040"

Beam Profiles

(Width x Height)

☐ 1-9/16" x 2-1/2"

☐ 1-9/16" x 6"

☐ 1-9/16" x 10"

☐ 1-9/16" x 3"

☐ 1-9/16" x 7"

☐ 1-9/16" x 11"

☐ 1-9/16" x 4"

☐ 1-9/16" x 8"

☐ 1-9/16" x 12"

☐ 1-9/16" x 5"

☐ 1-9/16" x 9"

☐ Other: _____

Beam Spacing

☐ 4"

☐ 6"

☐ 8"

☐ Other: _____

Color/Finish

☐ Cotton White - #0280

☐ Natural - #7163

☐ Other # _____

Perforation Pattern

☐ #106

☐ #115

☐ #119

☐ Other: _____

☐ Non-Perforated

Number of Sides Perforated

☐ One side

☐ Two sides

Acoustical Backer

☐ Black Non-Woven

☐ Black Polywrapped Pad

☐ None

End Caps

☐ Yes

☐ No

Grain Direction

(For Decorated End Caps)

☐ Horizontal

☐ Vertical

Exposure


☒ Interior Only

Shop Drawings required on all Tavola™ projects.

Perforations


Perforated panels improve acoustical performance as well as create aesthetic effects.

#106




Perforation dia: .098 in.
Open area: 16%

#115



Perforation dia: .063 in.
Open area: 12%

#119



Perforation dia: .098 in.
Open area: 8%

Physical Data

Substrates: Aluminum

Warranty: 1 year Limited Warranty

Seismic Application:

Contact CertainTeed Pre-Con Group for appropriate methods of addressing the specific application on your project.

Flame Spread / Smoke Dev.

Per ASTM E84 - CAN/ULC S102

Flame spread: ≤ 25 / Smoke Dev. ≤ 50
(Class A per ASTM E1264)

Weight: Varies 0.5 - 2.0 lbs./sq.ft.

Wind Load: N/A

Recycled Content: Up to 85%

**Light Reflectance (LR) Coefficient
per ASTM E1264 & ASTM E1477:**

- Cotton White LR = 0.81