

Specifications

Beckon

300262

Knoll Textiles

Application

Walls

Characteristics

Content: 76% Thermoplastic Olefin, 24% Post-Industrial Recycled Thermoplastic Olefin

Finish: PFAS-Free Protective Topcoat

Backing: Cotton Osnaburg/Polyester

Width: 52" (132cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment.

Price

Contact your sales representative for pricing.

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: ASTM E84 Adhered

CAN ULC S102 Adhered

EN 13501 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Specifications

Beckon

300262

Knoll Textiles

Environmental

Greenguard Gold Certified
LBC Red List Free
REACH Compliant
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS
Made In USA
HPD Available
BABA Compliant

Warranty


10 years.

© 2026 Maharam


Complete product information at maharam.com
800.645.3943



001 Fortright



002 Shaded



003 Charms



004 Flyaway



005 Patter




006 Zen



007 Mosey



008 Vitalize



009 Favor



010 Steeped



011 Etude



012 Sycamore



013 Nutria