Specifications
Ursa
300181

Knoll Textiles

Application
Walls

Characteristics
Content: 88% Non-Phthalate Vinyl, 12% Post-Industrial Recycled Non-Phthalate Vinyl
Finish: None
Backing: Polyester/Cotton Osnaburg
Width: 52" (132cm)
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price
Contact your sales representative for pricing.

Maintenance
W-Clean with water-based cleanser.

Testing
Flammability: ASTM E84 Adhered
CAN ULC S102 Adhered

Lightfastness: AATCC 16.3, 200+ hours



05.25

Specifications
Ursa
300181

Knoll Textiles

Environmental
Greenguard Certified
REACH Compliant
Contains Recycled Content
FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl
Made In USA

Warranty
10 years.

© 2024 Knoll, Inc.


Complete product information at knolltextiles.com
800.645.3943



001 Snowflake



002 Murmur



003 Tunnel



004 Swift



005 Volcanic



006 Emerge



007 Hush



008 Ambient


009 Poolside


010 Grateful


011 Odyssey



012 Alpaca


013 Sprinkle


014 Exact


015 Arid


016 Lychee


017 Sangria

05.25