

QUIET SIDE

FLEXFORM SOUND™ LVT

Luxury Vinyl Tile

Construction

High Performance Luxury Vinyl Tile
with Acoustic Backing

Finish

ProGuard MAX™

Wear Layer Thickness

22 mil (0.55 mm)

Overall Thickness

5.0 mm (0.197")

Edge Profile

Square

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Flexibility (ASTM F137)

Pass

Heat Stability by Color Change (ASTM F1514)

Pass

Light Stability (ASTM F1515)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

ASTM E492 IIC Rating

54 (6" no drop ceiling)

58 (8" no drop ceiling)

Dimensional Stability (ASTM F2199)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Static Load Limit (ASTM F970)

Pass

Installation

Direct Glue with Mosaic 95 only

Plank Size

6" x 48" (15.24 cm x 121.92 cm)

Pieces Per Box

12

Weight Per Box

37.04 lb (16.8 kg)

Quantity per Box

24 ft² (2.23 m²)

Recommended Installation Methods

Herringbone, Random

Warranty

22 Year Limited Commercial Wear Warranty

WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

ADHESIVE

For more information on our adhesive options, please visit our website. See installation instructions for more information on adhesive use.

