

LOST SIGNAL

FLEXFORM™ LVT – 2.5 mm

Luxury Vinyl Tile

Construction

High Performance Luxury Vinyl Tile

Finish

ProGuard™ Coating

Wear Layer Thickness

22 mil (0.55 mm)

Overall Thickness

2.5 mm (0.098")

Edge Profile

Square

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Flexibility (ASTM F137)

Pass

Heat Stability by Color Change (ASTM F1514)

Pass

Light Stability (ASTM F1515)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

Dimensional Stability (ASTM F2199)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Static Load Limit (ASTM F970)

Pass

Installation

Glue down

Tile Size

25 cm x 100 cm (9.84" x 39.37")

Pieces Per Box

16

Weight Per Box

37.6 lb (17.06 kg)

Quantity Per Box

42.9 ft² (3.99 m²)

Recommended Installation Method

Ashlar, Random, Herringbone

Warranty

15 Year Limited Commercial Wear Warranty

WARRANTIES

15 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

ADHESIVE

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.



Declare.

ORTHO-PHTHALATE
FREE

