

PRIMA

RIGIDFORM™ LVT

Resilient Tile

GENERAL

Construction

High Performance Rigid Core Tile

Finish

ProGuard™ Coating

Overall /Wear Layer Thickness

5.0mm/22 mil

Integrated Pad

1.0 mm IXPE pad

Edge Profile

Micro Bevel, with secure locking mechanism

PERFORMANCE

Critical Radiant Flux (ASTM E648)

Pass - Class I

Smoke Density (ASTM E662)

Pass - ≤ 450

Resistance to Heat (ASTM F1514)

Pass

Resistance to Light (ASTM F1515)

Pass

Resistance to Chemicals (ASTM F925)

Pass

Static Coefficient of Friction (ASTM D2047)

Pass

ASTM E492 IIC Rating

56 (6" no drop ceiling)

59 (8" no drop ceiling)

51 (18" OWT with ceiling)

TILE/PLANK SIZE

Tile/Plank Size

7" x 48"

9" x 60"

SHIPPING

Pieces Per Box

7" x 48": 10

9" x 60": 7

Weight Per Box

7" x 48": 44.8 lb (20.32 kg)

9" x 60": 47 lb (21.32 kg)

Quantity Per Box
7" x 48": 25.52 ft² (2.37 m²)9" x 60": 26.78 ft² (2.49 m²)
Quantity Per Pallet/Container
7" x 48": 48 cartons/pallet (1,225 ft²)20 pallets/container (24,502 ft²)9" x 60": 48 cartons/pallet (1,285 ft²)20 pallets/container (24,423 ft²)

INSTALLATION

Installation

Floating Floor

Recommended Installation Methods

Random

ADHESIVES

For more information on our adhesive options, please visit our website.

See *installation instructions* for more information on adhesive use.

WARRANTIES

15 Year Limited Commercial Wear


20 Year Limited Light Commercial Wear

- Multifamily Units & Hospitality Rooms Only

1 Year Manufacturing Defect Warranty

See *warranty document* for full details of terms and conditions

CERTIFICATIONS


Declare.

M/PACT™
CARBON NEUTRAL PROGRAM