FLOORING

Passages 26 | 3037



Product Specifications

Construction	Level Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	7172 oz./y3 (265.94 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	9.8 stitches/in (3.86 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	**PremierBac Plus** **Commercialon Premium Broadloom Adhesive** **Commercialon Premium Seam Sealer** **Encore® SD Ultima Fiber**
Optional Warranties	**Endure Plus** **TitanBac Plus** **Encore® 100 Fiber**


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	
Total Recycled Content	49.2%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2040 Avenue



2041 Vestibule



2042 Corridor



2043 Access




2044 Aisle



2045 Lane




2046 Channel



2047 Route




2048 Course



2049 Alley



2050 Pathway



2051 Trail