J+J FLOORING

Incognito Walk-off Modular | 7069



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

Construction	Textured Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD (with recycled content)
Face Weight	29 oz./sy (983 grams/m2)
Pile Density	8717 oz./y3 (323.23 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	12 stitches/in (4.72 stitches/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs, Advance Modular Carpet | Cushion Adhesive, Nexus Cushion Modular Adhesive
Standard Warranties	**Nexus Modular** **Commercialon Adhesive for Modular Carpet & LVT** **Encore® SD Ultima Fiber**
Optional Warranties	**Nexus Cushion Modular** **Nexus FC Cushion** **Advance Modular Backing** **Tile Tabs** **Nexus Cushion Adhesive** **Advance Modular Adhesive** **Encore® 100 Fiber**


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9716
Total Recycled Content	35.9%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



1837 Operative



1838 Espionage



1841 Intelligen...



1845 Cryptic