

 **BARRIER FREE**

**AFWALL™ FloWise™ ADA RETROFIT**

- Wall-mounted flushometer valve toilet
- Vitreous china
- Meets definition for HET (High Efficiency Toilet)
- High Efficiency (4.8 Lpf/1.28 gpf)
- EverClean™ anti-microbial surface which inhibits the growth of stain and odor causing bacteria, mold, and mildew
- Elongated bowl
- Powerful direct-fed siphon jet action
- Fully-glazed 2-1/8" trapway
- 10" x 12" water surface area
- Condensation channel
- 1-1/2" inlet spud
- 100% factory flush tested

- 3355.128** Elongated bowl only, top spud
- 3356.128** Elongated bowl only, top spud with slotted rim for bedpan holding (White only)
- 3357.128** Elongated bowl only, back spud
- 3358.128** Elongated bowl only, back spud with slotted rim for bedpan holding (White only)

Afwall ADA 1.28 replaces standard wall-hung 3.5 or 1.6 models and roughs-in at 410mm (16-1/8") rim height **to meet ADA with no need to modify the existing carrier or through wall supply** (providing centerline of current outlet is 133mm [5-1/4"] above finished floor).

**Component Parts:**

- 047007-0070A** Inlet spud (furnished with bowl)
- 736046-100** Flushometer valve rough-in adapter kit (furnished with bowl)

**Nominal Dimensions:**

660 x 356 x 419mm  
(26" x 14" x 16-1/2")

For Top spud bowls, American Standard kit #736046-100 Flushometer Valve Conversion Kit containing a 25mm (1") chrome-plated street ell, a vacuum breaker, and a 330mm (13") tail piece included to meet minimum 152mm (6") code between bowl and vacuum breaker.

Recommended working pressure—between 25 psi at valve when flushing and 80 psi static

Fixture only, less seat, carrier, bolt caps, and flushometer valve

**Compliance Certifications -**

**Meets or Exceeds the Following Specifications:**

- ASME A112.19.2 for Vitreous China Fixtures
- CAN/CSA International B45



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

**To Be Specified:**

- Color:  White  Bone  Silver  Linen
- Seat:
  - American Standard #5901.100 Heavy duty open front less cover
  - American Standard #5905.100 Extra heavy duty open front less cover
- Alternative Seat:
  - Olsonite #95 open front seat less cover
  - Church #9500C open front seat less cover
- Flushometer Valve:
  - American Standard Selectronic™ #6065.121.002 (Top Spud) Available Nov. 1, 2007
  - American Standard Selectronic™ #6065.222.007 (Concealed Back Spud) Available Nov. 1, 2007
- Alternative Flushometer Valve:
  - Sloan Crown #111-1.2 (Top Spud)



**MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES - CHECK LOCAL CODES.**

- When installed so top of seat is 432 to 483mm (17" to 19") from the finished floor.

