

# KOHLER®

## Roughing-In

**K-1124-H**  
**ARCHER™**

**6' (1.8 m) BATH WHIRLPOOL WITH HEATER**

### Product Information

Applicable product:				
Drop-in bath whirlpool with heater		K-1124-H		
Fixture*:				
Bathing well				
Basin area bottom	51-3/8" (130.5 cm) x 21" (53.3 cm)			
Basin area top	64-1/2" (163.8 cm) x 30-1/2" (77.5 cm)			
Weight	110 lbs (50 kg)			
To overflow				
Water depth	15" (38.1 cm)			
Capacity	72 gal (273 L)			
* Approximate measurements for comparison only.				
Drop-in cutout dimensions:				
70-1/2" (179.1 cm) x 34-1/2" (87.6 cm)				
Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Pump is supplied with 24" (61 cm) grounding-type plug-in cord.

Minimum access panel pump/control:

20" (50.8 cm) W x 15" (38.1 cm) H required

### Required Electrical Service (2 required)

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 41 lbs/square foot (201 kg/square meter) loading.

This product is designed for drop-in installation only. It is not intended for use in a three-wall alcove with an overhead shower.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7272)

