

# KOHLER® Roughing-In

## K-1154-H, K-1154-FH PROFLEX® 5454 ACRYLIC BATH WHIRLPOOL WITH HEATER

### Product Information

Applicable product:	
Bath whirlpool, drop-in rim style, right-hand pump	K-1154-H
Bath whirlpool, tile flange, right-hand pump	K-1154-FH

Recommended accessories:	
Cable drain with PVC tubing	K-7213
Cable drain without PVC tubing	K-7214
Trip lever drain	K-11677

Fixture*:	
Basin area:	
Bathing well	44" (111.8 cm) x 36" (91.4 cm)
Top area	56" (142.2 cm) x 43" (109.2 cm)
To overflow:	
Water depth	15" (38.1 cm)
Capacity	76 gal (288 L)
Weight	70 lbs (31.8 kg)
* Approximate measurements for comparison only.	

Pump:	Hp	V	Hz	A
1-speed	1.25	120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater:	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 36 lbs/square foot (176 kg/square meter) loading.

No change in measurements if connected with drain illustrated. (K-11677)

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

