

## **Product Information**

Applicable product:  Bath whirlpool, drop-in rim style, custom K-1257-CB					
Bath whirlpool, drop-in rim style, custom pump			lom	K-1257-CB	
Pamp					
Recommended a	ccessorie	s:			
Drain			K	K-7166-AF	
Fixture*:					
Basin area:					
Bathing well	50" (127 cm) x 24" (61 cm)				
Top area	65" (165.1 cm) x 27" (68.6 cm)				
To overflow:					
Water depth	14" (35.6 cm)				
Capacity	72 gal (272.5 L)				
Weight	110 lbs (49.9 kg)				
Drop-in cut-out	70" (177.8 cm) x 34" (86.4 cm)				
* Approximate m	easureme	nts for cor	npariso	n only.	
Pump:	Нр	V	Hz	А	
1-speed	1.25	120	60	7.5	

## **Required Electrical Service**

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):				
Pump/control	120 V, 15 A, 60 Hz			
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.				

## **Installation Notes**

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (200 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

