

KOHLER® Roughing-In

K-1245
SOJOURN™
ACRYLIC BATH

Ordering Information

Applicable product:		
Drop-in rim style	K-1245	shown
Integral flange	K-1245-F	not shown
Accessories/hardware:		
Drain	K-7161-AF	recommended
Apron	K-1243	optional
Vinyl tiling-in bead*	K-1179	optional
*Use K-1179 vinyl bead when wall material contacts any top surface of the drop-in rim style bath.		

Product Information

Fixture*:	basin area	top area	weight
Bathing well	50" x 42"	60" x 46"	91 lbs.
	water depth	capacity	
To overflow	14-1/2"	102 gal.	
* Approximate measurements for comparison only.			

Included Components:

Cutout template, top	1000550-7
Cutout template, bottom	1000551-7

Installation Notes

Refer to installation instructions included with fixture before beginning installation.

NOTICE: Unless otherwise specified, floor support under bath must provide for a minimum of 80 lbs./square foot loading.

If installing a rim-mount faucet, make sure there is no interference with drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finish floor and wall materials are installed.

Roughing-In Notes

Fixture conforms to ANSI Standard Z124.1. All dimensions are nominal.

No change in measurements if connected with drain illustrated.

Faucet area		recommended
-------------	--	-------------

