KOHLER®

Roughing-In

K-4450-C
STRATTON™
WATER-GUARD® BOWL

Product Information

Applicable product:	
Elongated bowl toilet	K-4450-C
Elongated bowl toilet with bedpan lugs	K-4450-CL
Fixture is ADA compliant when installed at required height of 17″ (43.2 cm) - 19″ (48.3 cm) from floor to top of seat. ADA	

Fixture:	
Configuration	Top spud, elongated
Water per flush	3.5 gal (13.2 L)*
Spud size	1-1/2″
Passageway	2-3/4″ (7 cm)
Water area	14-1/2″ (36.8 cm) x 11-3/8″ (28.9 cm)
Water depth from rim	5-3/8″ (13.7 cm)
Seat post hole centers	5-1/2″ (14 cm)
Minimum running pressure required	25 psi (172.4 kPa)
* Designed to flush with 3.5 gal (13.2 L) of water when installed with a 3.5 gpf (13.2 lpf) valve.	

Recommended accessories:	
Lustra™ open front seat	K-4670-C
Lustra open front seat with anti-microbial agent	K-4670-CA

Included components:	
Spud	18357

Installation Notes

Install this product according to the installation guide.

Refer to manufacturer and local codes for flush valve requirements.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.