

KOHLER®

Roughing-In

K-4405
HIGHLINE™
HIGH EFFICIENCY BOWL

Product Information

Applicable product:	
Elongated bowl toilet	K-4405
Elongated bowl toilet with bedpan lugs	K-4405-L
Fixture is ADA compliant. ADA	
Fixture:	
Configuration	Top spud, elongated
Water per flush	1.28 gallons (4.85 L)*
Spud size	1-1/2" (3.8 cm)
Passageway	2-1/4" (5.7 cm)
Water area	11" (27.9 cm) x 9" (22.9 cm)
Water depth from rim	6" (15.2 cm)
Seat post hole centers	5-1/2" (14 cm)
* Designed to flush with 1.28 gallons (4.85 L) of water when installed with a 1.28 gpf (4.85 lpf) valve.	

Recommended accessories:

EB open front seat with check hinge	K-4731-C
EB open front seat with self-sustaining check hinge	K-4731-SC
Lustra™ open front seat with support arms and cover	K-4654
Lustra open front seat (with anti-microbial agent)	K-4670-CA
Lustra™ open front seat with support arms and cover (with anti-microbial agent)	K-4654-A
1.28 gpf (4.85 lpf) Touchless™ DC toilet flushometer with Tripoint™ technology	K-10956

Included components:

Spud	18357
Bolt cap accessory pack	1013092

Flush valve requirements: For 12" (30.5 cm) rough-in, sweat extension nipple is required. Refer to manufacturer and local codes.

Installation Notes

Install this product according to the installation guide.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.

