

REVIVAL®

Features


- Brass construction
- Brass valve bodies
- · Quarter-turn washerless ceramic disc valves
- Available with scroll or traditional handle(s)
- Handspray
- Flexible connections for easy installation
- 2.2 gallons (8.3 L) per minute maximum flow rate
- Lower flow aerator options are available (refer to the Kohler Price Book)
- 9-3/16" (23.3 cm) swing spout

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- NSF 61
- Energy Policy Act of 1992
- ADA

KITCHEN SINK FAUCET K-16109



Colors/Finishes

- CP: Polished Chrome
- BN: Brushed Nickel
- BX: Vibrant® Brazen Bronze
- Other: Refer to Price Book for additional colors/finishes

Accessories

• NA: None applicable

Specified Model

Model	Description	ADA			ADA			
K-16109-4	Faucet with scroll handles and handspray	□СР	□ BN	Other				
K-16109-4A	Faucet with traditional handles and handspray				□ CP	□BN	□BX	□ Other
Optional Accessories								
77619	Deep roughing-in kit for 2-handle (only) kitchen faucets							NA
1011402	Sidespray deep roughing-in kit							NA
40003	Wrench for long-stemmed ceramic valve bodies							NA

Product Specification

The two-handle kitchen sink faucet shall be of brass construction. Faucet shall feature brass valve bodies. Faucet shall feature quarter-turn washerless ceramic disc valves, assuring positive handle stop positioning. Faucet shall have a flow rate of 2.2 gallons (8.3 L) per minute with lower flow aerator options available. Faucet shall feature 8" (20.3 cm) centers, 9-3/16" (23.3 cm) swing spout, handspray, and flexible connections for easy installation. Faucet shall feature ADA compliant traditional or scroll handles. Faucet shall be Kohler Model K-16109-____-___.

REVIVAL®

Installation Notes

Install this product according to the installation guide.

