


oxygen

emergency ceiling mounts

type

oracle EM ceiling mount	series#	lamping	dimensions	finishes		EM ballast	
 • acrylic diffuser	2-6142	1 x 22W + 1 x 32W T9 circline fluorescent	D = 17.69" H = 5.56"	24	satin nickel	EM*	integral emergency ballast
 • acrylic diffuser	2-6143	1 x 32W + 1 x 40W T9 circline fluorescent	D = 23.50" H = 6.24"				
general specifications							

- Formed steel trim.
- Cold rolled steel housing.
- 1/16" white acrylic diffusers are standard.
- U.L and C.U.L. approved for dry locations.
- Fluorescent ballast is electronic HPF, instant start, 120V.
- All units mount to 4" octagonal junction box. Unless otherwise noted, no additional supports required.
- Visit www.oxygenlighting.com for technical cut sheets.
- Oxygen lighting reserves the right to modify designs at any time.
- * • Unless otherwise specified, a Bodine ballast will be used. Only EM ballasts with an "F-can" hole pattern may be installed.

sample catalog number			
series #	finish	EM ballast	catalog number
<u>2-6142</u>	-	<u>24</u> - <u>EM</u>	= <u>2-6142-24-EM</u>
oracle EM flush mount, 1 x 22W + 1 x 32W T9 circline	satin nickel	integral emergency ballast	



